



UNITS: INCHES

| FRAME SIZE | MOTOR DIMENSIONS | | | | | | | | | | | CONDUIT BOX | | | | | | |
|------------|------------------|------|------|-------|-----|-----|-----|------|------|------|-----|-------------|------|------|------|-----|------|------|
| | A | B | C | D | G | J | K | M | O | P | T | AA | AB | AC | AE | AF | XL | XN |
| 444T | 22.1 | 17.4 | 37.8 | 11.00 | 0.9 | 4.4 | 4.8 | 14.6 | 22.5 | 22.0 | 3.6 | 3.00 | 21.6 | 16.5 | 14.2 | 8.7 | 15.7 | 11.5 |

| FRAME SIZE | MOUNTING | | | SHAFT EXTENSION | | | KEY SEAT | | | BEARINGS | | MAXIMUM WEIGHT | |
|------------|----------|-------|------|-----------------|------|------|----------|-------|-------|----------|---------|----------------|-----------|
| | E | 2F | H | BA | N-W | V | U | R | S | ES | LS | | OS |
| 444T | 9.00 | 14.50 | 0.81 | 7.50 | 8.50 | 8.25 | 3.375 | 2.880 | 0.875 | 6.88 | NU318C3 | 6318C3 | 1490 lbs. |

NOTES:

1. DIMENSION V REPRESENTS LENGTH OF STRAIGHT PART OF SHAFT
2. MAIN CONDUIT BOX MAY BE ROTATED IN 90° INCREMENTS
3. KEY DIMENSIONS EQUAL S x S x 6.88 (MOTOR SUPPLIED WITH KEY)
4. MOTOR WEIGHT SHOWN IS MAXIMUM HORSEPOWER IN FRAME
5. OPPOSITE ROTATION AVAILABLE ONLY BY CONNECTION CHANGE

CUSTOMER: _____ MOTOR MODEL NO.: 0758DPSA21A-R
 P.O. NO.: _____ HP: 75 VOLTAGE: 230/460 RPM(SYN.): 900 Hz: 60
 FRAME SIZE: 444T PRODUCT TYPE: ODP EQP III, EPACT, & HIGH EFFICIENCY
 COMMENTS: _____

TAG NO's.: _____

- STANDARD (NO AUX. BOXES)
- RTD AUX. BOX
- SPACE HEATER AUX. BOX
- BEARING RTD's

PER: _____ DATE: _____

TOSHIBA RESERVES THE RIGHT TO MAKE CHANGES OF TECHNICAL IMPROVEMENT AND THE DATA MAY CHANGE WITHOUT NOTICE PRELIMINARY

DO NOT USE FOR CONSTRUCTION, INSTALLATION, OR APPLICATION PURPOSES UNLESS THE DRAWING IS MARKED AS CERTIFIED CERTIFIED

TOSHIBA

TOSHIBA INTERNATIONAL CORPORATION

OPEN DRIP-PROOF
 HORIZONTAL FOOT-MOUNTED
 3 PHASE INDUCTION MOTOR
 F1 ASSEMBLY

XT SERIES

VISIT OUR WEBSITE AT:
www.toshiba.com/ind