



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET

Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : P-Base Motors : High Efficiency

Frame : 143HP
Output : 1.5 HP
Frequency : 60 Hz
Poles : 2
Full load speed : 3480 rpm
Slip : 3.33 %
Voltage : 230/460 V
Rated current : 4.14/2.07 A
Locked rotor current : 35.2/17.6 A
Locked rotor current (I_L/I_N) : 8.5
No-load current : 2.00/1.00 A
Full load torque : 2.23 lb.ft
Locked rotor torque : 300 %
Breakdown torque : 400 %
Design : B
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 15 s (hot)
Service factor : 1.25
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 42 lb
Moment of inertia : 0.03607 sq.ft.lb
Noise level : 68 dB(A)

	D.E.	N.D.E.
Bearings	6307 ZZ	6204 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.81	82.5
75%	0.74	81.5
50%	0.64	78.5

Notes:

Downloaded from <http://dealerselectric.com>
Generated for Model #00156EP3E143HP

Performed by

Checked