

# PRODUCT INFORMATION PACKET



Model No: H988L

Catalog No: H988L

3.0 HP Circulator pump Motor, 3 phase, 1800 RPM, 460/208-230 V, 56Y Frame, ODP  
Circulator Pump Motors



Regal and Century are trademarks of Regal Beloit Corporation or one of its affiliated companies.

©2019 Regal Beloit Corporation, All Rights Reserved. MC017097E

REGAL



**Nameplate Specifications**

Output HP	3.0 Hp	Output KW	2.2 kW
Frequency	60 Hz	Voltage	460/208-230 V
Current	4.4/9.0-8.8 A	Speed	1725 rpm
Service Factor	1.15	Phase	3
Duty	Continuous	Insulation Class	F
Frame	R56Y	Enclosure	Drip Proof
Thermal Protection	None	Ambient Temperature	40 °C
UL	Recognized	CSA	Y
CE	N		

**Technical Specifications**

Electrical Type	Polyphase, Induction Type, Single Or Dual Voltage	Starting Method	Across The Line
Poles	4	Rotation	Reversible Counterclockwise
Mounting	Cushion Ring	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Rolled Steel
Shaft Type	Keyed	Overall Length	14.56 in
Frame Length	8.75 in	Shaft Diameter	0.875 in
Shaft Extension	2.31 in		

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:04/11/2019