

PRODUCT INFORMATION PACKET



Model No: SRD4B0.5T65

Catalog No: LM34062

..1/2HP..1800RPM.S56.ODP.575V.3PH.60HZ.CONT.40C.1.25S.F..RIGID.....GENERAL PURPOSE.NOT.....
575 Volts



Regal and Leeson are trademarks of Regal Beloit Corporation or one of its affiliated companies.

©2018 Regal Beloit Corporation, All Rights Reserved. MC017097E





Nameplate Specifications

Output HP	0.50 Hp	Output KW	0.37 kW
Frequency	60 Hz	Voltage	575 V
Current	0.70 A	Speed	1725 rpm
Service Factor	1.25	Phase	3
Efficiency	78.2 %	Duty	Continuous
Insulation Class	B	Design Code	B
KVA Code	LATER	Frame	56
Enclosure	Drip Proof	Overload Protector	No
Ambient Temperature	40 °C	Drive End Bearing Size	6203
Opp Drive End Bearing Size	6203	UL	Recognized
CSA	Y	CE	Y
IP Code	22		

Technical Specifications

Electrical Type	Squirrel Cage Inverter Rated	Starting Method	Line Or Inverter
Poles	4	Rotation	Reversible
Mounting	Rigid base	Motor Orientation	HORIZONTAL
Drive End Bearing	BALL	Opp Drive End Bearing	BALL
Frame Material	Rolled Steel	Shaft Type	T
Overall Length	11.32 in	Frame Length	5.50 in
Shaft Diameter	0.625 in	Shaft Extension	1.88 in
Assembly/Box Mounting	F1 ONLY		
Outline Drawing	LM34062	Connection Diagram	D0000566-001

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created: 10/15/2018