PRODUCT INFORMATION PACKET



Model No: 056E17F1007 Catalog No: Z610 3/4,1750,TEFC,56C,DC/90 SCR



Regal and Marathon are trademarks of Regal Beloit Corporation or one of its affiliated companies.

©2018 Regal Beloit Corporation, All Rights Reserved. MC017097E





Nameplate Specifications

Output HP0.75 HpOutput KW0.56 kWVoltage90 VCurrent7.6 ASpeed1750 rpmService Factor1Efficiency84.2 %DutyContinousInsulation ClassFFrameUSS56CEnclosureTotally Enclosed Fan CooledOverload ProtectorNoAmbient Temperature40 °CULRecognizedCSAYCEN				
Speed1750 rpmService Factor1Efficiency84.2 %DutyContinousInsulation ClassFFrameUSS56CEnclosureTotally Enclosed Fan CooledOverload ProtectorNoAmbient Temperature40 °CULRecognized	Output HP	0.75 Hp	Output KW	0.56 kW
Efficiency84.2 %DutyContinousInsulation ClassFFrameUSS56CEnclosureTotally Enclosed Fan CooledOverload ProtectorNoAmbient Temperature40 °CULRecognized	Voltage	90 V	Current	7.6 A
Insulation Class Frame USS56C Enclosure Totally Enclosed Fan Cooled Overload Protector No Ambient Temperature 40 °C UL Recognized	Speed	1750 rpm	Service Factor	1
Enclosure Totally Enclosed Fan Cooled Overload Protector No Ambient Temperature 40 °C UL Recognized	Efficiency	84.2 %	Duty	Continous
Ambient Temperature 40 °C UL Recognized	Insulation Class	F	Frame	USS56C
	Enclosure	Totally Enclosed Fan Cooled	Overload Protector	No
CSA Y CE N	Ambient Temperature	40 °C	UL	Recognized
	CSA	Υ	CE	N

Technical Specifications

Rotation	Counterclockwise Lead End	Mounting	Rigid C base
Frame Length	9.50 in	Shaft Diameter	0.625 in
Outline Drawing	027811-950		

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created: 07/02/2018