NEMA Premium

# NEMA

| MOTOR MODEL: | BR3-CI-TF-254TC-2-BR-E-15 |
|---|---|
| FACTORY TYPE: | TXC |

## Premium NEMA Cast Iron, TEFC

| ELECTRICAL DATA | | |
|---|---|---|
| | 60 Hz | 50 Hz |
| Horsepower | 15.0 | 15.0 |
| Speed, RPM | 3540 | 2920 |
| Voltage | 460 | 380 |
| # Phase | 3 | |
| Full Load Amps | 17.6 | - |
| Power Factor | 0.88 | - |
| Nominal Efficiency | 91.0 | 88.0 |
| 3/4 Load Efficiency | - | - |
| Service Factor | 1.25 | 1.0 |
| KVA Code | L | F |
| FL Amps. @ 208 V | - | - |
| LRC @ 60Hz HV | 208.506 | - |
| Start Capacitor | - | |
| Start Capacitor V | - | |
| Run Capacitor | - | |
| Run Capacitor V | - | |
| Number of Leads | 12 | |
| Connection | DD/D | |
| Coil Resistance | - | |
| Date Code | - | |

| Load | Efficiency % | P.F. |
|---|---|---|
| 50% | 87.1 | 0.71 |
| 75% | 89.66 | 0.81 |
| 100% | 90.53 | 0.86 |

| FULL LOAD TEMPERATURE RISE | | |
|---|---|---|
| FL Temp Rise °C | 52.0 | - |

| 3D Image Link |
|---|
| BR3-CI-TF-254TC-2-BR-E-15 |

*This report valid for above Date Code and newer models, please contact Techtop for more info.

| GENERAL DATA | |
|---|---|
| Frame Size | 254TC |
| Frame Enclosure | TEFC |
| Mounting | Rigid/C-Flange |
| Insulation Class | F |
| Duty | Cont. / S1 |
| NEMA Design | A |
| Frame Material | Cast Iron |
| Ingress Protection | 56 |
| Tropicalization | true |
| Cable Entry | 1-NPT 1-1/4" |
| Feet Removable | true |
| Double Drilled | - |
| Paint Color | Graphite Gray |
| Paint RAL | 7024 |
| Weight lb | 254.678 |

| MECHANICAL DATA | |
|---|---|
| DE Bearing | 6309C3 |
| NDE Bearing | 6309C3 |
| dB No-Load | - |
| Rotor Wk², Lb-Ft² | - |
| Comp Ring (wavey washer) | - |

| TORQUE VALUES | Torque lb-ft | % FLT |
|---|---|---|
| Locked Rotor Torque | 75.0398 | 337.0 |
| Pull-Up Torque | 42.9753 | 193.0 |
| Breakdown Torque | 88.1773 | 396.0 |
| Full Load Torque | 22.267 | 100.0 |

| SITE CONDITIONS | |
|---|---|
| Ambient Temp °C | 40 |
| Altitude Above Sea Level m | 1000 |


Techtop Industries
2815 Colonnades Court
Peachtree Corners, GA 30071
Tel: 678-436-5540
E-Mail: info@techtopind.com

NEMA Premium

| | |
|---|---|
| **MOTOR MODEL:** | BR3-CI-TF-254TC-2-BR-E-15 |
| **FACTORY TYPE:** | TXC |

# NEMA

## Premium NEMA Cast Iron,  TEFC




Performance Load Values, High Voltage, 60Hz

| Torque Values | Torque lb-ft | % FLT | Performance Values | |
|---|---|---|---|---|
| Locked Rotor Torque | 75.0398 | 337.0 | Start Configuration | - |
| Pull-Up Torque | 42.9753 | 193.0 | Starting Current (A) | - |
| Breakdown Torque | 88.1773 | 396.0 | No-Load Current (A) | - |
| Full Load | 22.267 | 100.0 | No-Load Power Factor | - |

| % Load | Horsepower | Current, Amps | Input power, Kilowatts | Speed, RPM | Efficiency | PF |
|---|---|---|---|---|---|---|
| 0 | - | 8.01 | - | - | - | - |
| 25 | 3.75 | 9.11 | 3.58 | 3592.6 | 78.93 | 0.49 |
| 50 | 7.5 | 11.59 | 6.49 | 3585.6 | 87.1 | 0.71 |
| 75 | 11.25 | 14.7 | 9.45 | 3578.2 | 89.66 | 0.81 |
| 100 | 15.0 | 18.29 | 12.48 | 3570.4 | 90.53 | 0.86 |
| 125 | 18.75 | 22.21 | 15.58 | 3562.3 | 90.67 | 0.88 |

Techtop Industries
2815 Colonnades Court
Peachtree Corners, GA 30071
Tel: 678-436-5540
E-Mail: info@techtopind.com