NEMA Premium

NEMA

MOTOR MODEL:	BR3-CI-TF-326T-4-BR-E-50
FACTORY TYPE:	TXC

Premium NEMA Cast Iron, TEFC

ELECTRICAL DATA		
	60 Hz	50 Hz
Horsepower	50.0	50.0
Speed, RPM	1770	1460
Voltage	460	380
# Phase	3	
Full Load Amps	59.2	68
Power Factor	0.87	-
Nominal Efficiency	94.5	91.5
3/4 Load Efficiency	-	-
Service Factor	1.25	1.0
KVA Code	K	E
FL Amps. @ 208 V	-	-
LRC @ 60Hz HV	613.812	-
Start Capacitor	-	
Start Capacitor V	-	
Run Capacitor	-	
Run Capacitor V	-	
Number of Leads	12	
Connection	DD/D	
Coil Resistance	-	
Date Code	-	
Load	**Efficiency %**	**P.F.**
50%	93.78	0.71
75%	94.29	0.81
100%	94.03	0.85
FULL LOAD TEMPERATURE RISE		
FL Temp Rise °C	82.0	-
3D Image Link		
BR3-CI-TF-326T-4-BR-E-50		

*This report valid for above Date Code and newer models, please contact Techtop for more info.

GENERAL DATA	
Frame Size	326T
Frame Enclosure	TEFC
Mounting	Rigid
Insulation Class	F
Duty	Cont. / S1
NEMA Design	A
Frame Material	Cast Iron
Ingress Protection	56
Tropicalization	true
Cable Entry	1-NPT 2"
Feet Removable	true
Double Drilled	true
Paint Color	Graphite Gray
Paint RAL	7024
Weight lb	600.862
MECHANICAL DATA	
DE Bearing	6312C3
NDE Bearing	6312C3
dB No-Load	-
Rotor Wk², Lb-Ft²	-
Comp Ring (wavey washer)	DE

TORQUE VALUES	Torque lb-ft	% FLT
Locked Rotor Torque	506.56	299.0
Pull-Up Torque	333.754	197.0
Breakdown Torque	520.113	307.0
Full Load Torque	169.418	100.0
SITE CONDITIONS		
Ambient Temp °C	40	
Altitude Above Sea Level m	1000	


Techtop Industries
2815 Colonnades Court
Peachtree Corners, GA 30071
Tel: 678-436-5540
E-Mail: info@techtopind.com

NEMA Premium

MOTOR MODEL:	BR3-CI-TF-326T-4-BR-E-50
FACTORY TYPE:	TXC

NEMA

Premium NEMA Cast Iron, TEFC



Performance Load Values, High Voltage, 60Hz

Torque Values	Torque lb-ft	% FLT	Performance Values	
Locked Rotor Torque	506.56	299.0	Start Configuration	-
Pull-Up Torque	333.754	197.0	Starting Current (A)	-
Breakdown Torque	520.113	307.0	No-Load Current (A)	-
Full Load	169.418	100.0	No-Load Power Factor	-

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	26.53	-	-	-	-
25	12.5	30.25	11.84	1795.2	90.58	0.49
50	25.0	40.19	22.87	1790.5	93.78	0.71
75	37.5	52.63	34.12	1785.5	94.29	0.81
100	50.0	67.01	45.63	1780.2	94.03	0.85
125	62.5	82.79	57.41	1774.4	93.41	0.87

Techtop Industries
2815 Colonnades Court
Peachtree Corners, GA 30071
Tel: 678-436-5540
E-Mail: info@techtopind.com