NEMA Premium

# NEMA

| MOTOR MODEL: | BR3-CI-TF-364TC-6-BR-E-40 |
|---|---|
| FACTORY TYPE: | TXC |

## Premium NEMA Cast Iron, TEFC

| ELECTRICAL DATA | | |
|---|---|---|
| | 60 Hz | 50 Hz |
| Horsepower | 40.0 | 40.0 |
| Speed, RPM | 1180 | 980 |
| Voltage | 460 | 380 |
| # Phase | 3 | |
| Full Load Amps | 47.4 | - |
| Power Factor | 0.84 | - |
| Nominal Efficiency | 94.1 | 92.5 |
| 3/4 Load Efficiency | - | - |
| Service Factor | 1.15 | 1.0 |
| KVA Code | J | E |
| FL Amps. @ 208 V | - | - |
| LRC @ 60Hz HV | - | - |
| Start Capacitor | - | |
| Start Capacitor V | - | |
| Run Capacitor | - | |
| Run Capacitor V | - | |
| Number of Leads | 12 | |
| Connection | DD/D | |
| Coil Resistance | - | |
| Date Code | - | |
| | | |
| **Load** | **Efficiency %** | **P.F.** |
| 50% | - | - |
| 75% | - | - |
| 100% | - | - |
| | | |
| **FULL LOAD TEMPERATURE RISE** | | |
| FL Temp Rise °C | - | - |
| | | |
| **3D Image Link** | | |
| BR3-CI-TF-364TC-6-BR-E-40 | | |

*This report valid for above Date Code and newer models, please contact Techtop for more info.

| GENERAL DATA | |
|---|---|
| Frame Size | 364TC |
| Frame Enclosure | TEFC |
| Mounting | Rigid/C-Flange |
| Insulation Class | F |
| Duty | Cont. / S1 |
| NEMA Design | A |
| Frame Material | Cast Iron |
| Ingress Protection | 56 |
| Tropicalization | true |
| Cable Entry | 1-NPT 2" |
| Feet Removable | - |
| Double Drilled | - |
| Paint Color | Graphite Gray |
| Paint RAL | 7024 |
| Weight lb | 725.445 |
| | |
| **MECHANICAL DATA** | |
| DE Bearing | 6313C3 |
| NDE Bearing | 6313C3 |
| dB No-Load | - |
| Rotor Wk², Lb-Ft² | - |
| Comp Ring (wavey washer) | - |

| TORQUE VALUES | Torque lb-ft | % FLT |
|---|---|---|
| Locked Rotor Torque | - | - |
| Pull-Up Torque | - | - |
| Breakdown Torque | - | - |
| Full Load Torque | - | 100.0 |

| SITE CONDITIONS | |
|---|---|
| Ambient Temp °C | 40 |
| Altitude Above Sea Level m | 1000 |

Techtop Industries
2815 Colonnades Court
Peachtree Corners, GA 30071
Tel: 678-436-5540
E-Mail: info@techtopind.com