



NEMA Premium

NEMA

MOTOR MODEL:	GR3-RS-OP-182T-2-B-D-5
FACTORY TYPE:	-

NEMA Rolled Steel, ODP

ELECTRICAL DATA		
	60 Hz	50 Hz
Horsepower	5.0	-
Speed, RPM	3510	2865
Voltage	230/460	190/380
# Phase	3	
Full Load Amps	11.9/5.95	-
Power Factor	0.9	-
Nominal Efficiency	87.5	-
3/4 Load Efficiency	-	-
Service Factor	1.25	1.0
KVA Code	J	F
FL Amps. @ 208 V	13.1	-
LRC @ 60Hz HV	-	-
Start Capacitor	-	
Start Capacitor V	-	
Run Capacitor	-	
Run Capacitor V	-	
Number of Leads	9	
Connection	YY/Y	
Coil Resistance	1.6	
Date Code	-	
Load	Efficiency %	P.F.
50%	88.54	0.8319
75%	89.04	0.8951
100%	88.19	0.9155
FULL LOAD TEMPERATURE RISE		
FL Temp Rise °C	35.0	61.0
3D Image Link		
GR3-RS-OP-182T-2-B-D-5		

GENERAL DATA		
Frame Size	182T	
Frame Enclosure	ODP	
Mounting	Rigid	
Insulation Class	F	
Duty	Cont. / S1	
NEMA Design	-	
Frame Material	Rolled Steel	
Ingress Protection	23	
Tropicalization	true	
Cable Entry	1-NPT 3/4"	
Feet Removable	-	
Double Drilled	-	
Paint Color	Graphite Gray	
Paint RAL	7024	
Weight lb	-	
MECHANICAL DATA		
DE Bearing	6206ZZ	
NDE Bearing	6205ZZ	
dB No-Load	-	
Rotor Wk ² , Lb-Ft ²	-	
Comp Ring (wavy washer)	NDE	
TORQUE VALUES		
	Torque lb-ft	% FLT
Locked Rotor Torque	14.29	190.0
Pull-Up Torque	10.53	140.0
Breakdown Torque	22.56	300.0
Full Load Torque	7.52	100.0
SITE CONDITIONS		
Ambient Temp °C	-	
Altitude Above Sea Level m	-	

*This report valid for above Date Code and newer models, please contact Techttop for more info.

Techtop Industries
2815 Colonnades Court
Peachtree Corners, GA 30071
Tel: 678-436-5540
E-Mail: info@techttopind.com




NEMA Premium

NEMA

MOTOR MODEL:	GR3-RS-OP-182T-2-B-D-5
FACTORY TYPE:	-

NEMA Rolled Steel, ODP

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

Torque Values	Torque lb-ft	% FLT	Performance Values	
Locked Rotor Torque	14.29	190.0	Start Configuration	-
Pull-Up Torque	10.53	140.0	Starting Current (A)	-
Breakdown Torque	22.56	300.0	No-Load Current (A)	-
Full Load	7.52	100.0	No-Load Power Factor	-

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	-	-	-	-	-
25	-	-	-	-	-	-
50	-	-	-	-	88.54	0.8319
75	-	-	-	-	89.04	0.8951
100	-	-	-	-	88.19	0.9155
125	-	-	-	-	-	-

Techtop Industries
 2815 Colonnades Court
 Peachtree Corners, GA 30071
 Tel: 678-436-5540
 E-Mail: info@techttopind.com