

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer : Dealers Industrial Equipment 800-469-3110
Customer reference : 07518OP3EFP365TC-W40

Product line : W40 High Efficiency Three-Phase Product code : 14281214
Catalog # : 07518OP3EFP365TC-W40

Frame	: 364/5TC	Locked rotor time	: 34s (cold) 19s (hot)
Output	: 75 HP (55 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 208-230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 189-171/85.3 A	Protection degree	: IP23
L. R. Amperes	: 1188-1075/537 A	Cooling method	: IC01 - ODP
LRC	: 6.3x(Code G)	Mounting	: F-1
No load current	: 43.1-50.0/25.0 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1775 rpm	Starting method	: Direct On Line
Slip	: 1.39 %	Approx. weight ³	: 774 lb
Rated torque	: 219 ft.lb		
Locked rotor torque	: 180 %		
Breakdown torque	: 229 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 15.2 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	93.5	93.6	94.1	94.1	Max. traction	: 1626 lb
Power Factor	0.52	0.75	0.83	0.86	Max. compression	: 2400 lb

	Drive end	Non drive end
Bearing type	: 6314 C3	: 6212 Z C3
Sealing	: Without Bearing Seal	: Without Bearing Seal
Lubrication interval	: 20000 h	: 20000 h
Lubricant amount	: 27 g	: 13 g
Lubricant type	Mobil Polyrex EM	

Notes
downloaded from <http://dealerselectric.com>

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	14/04/2019			

Page 1 / 2
Revision


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : Dealers Industrial Equipment 800-469-3110
Customer reference : 07518OP3EFP365TC-W40

Product line : W40 High Efficiency Three-Phase Product code : 14281214
Catalog # : 07518OP3EFP365TC-W40




Performance : 208-230/460 V 60 Hz 4P


Rated current : 189-171/85.3 A LRC : 6.3 Rated torque : 219 ft.lb Locked rotor torque : 180 % Breakdown torque : 229 % Rated speed : 1775 rpm	Moment of inertia (J) : 15.2 sq.ft.lb Duty cycle : Cont.(S1) Insulation class : F Service factor : 1.15 Temperature rise : 80 K Design : B
--	---

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date					

THIS IS AN UPDATED REVISION, THE
PREVIOUS ONE MUST BE DISREGARDED.



SCALE	1:8
-------	-----

ECM	LOC	SUMMARY OF MODIFICATIONS		EXECUTED	CHECKED	RELEASED	DATE	VER
EXECUTED	USERADMIN		THREE PHASE W40 MOTOR HIGH EFF					
CHECKED			FRAME 364/5TC IP23 ODP					
RELEASED			WEG code: 14281214					
REL DT	14.04.2019	WMO	Jaragua do Sul	Product Engineering	SHEET	1 / 1		

75 HP 04 Poles 60Hz

A

WEG's property. Forbidden reproduction without previous authorization.

ZME	A3
-----	----