

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer : Dealers Industrial Equipment 800-469-3110
Customer reference : 12536OP3HFP404TS-W40

Product line : W40 High Efficiency Three-Phase Product code : 14282771
Catalog # : 12536OP3HFP404TS-W40

Frame	: 404/5TS	Locked rotor time	: 27s (cold) 15s (hot)
Output	: 125 HP	Temperature rise	: 105 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 110 A	Protection degree	: IP23
L. R. Amperes	: 723 A	Cooling method	: IC01 - ODP
LRC	: 6.6x(Code G)	Mounting	: F-1
No load current	: 24.0 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3545 rpm	Noise level ²	: 84.0 dB(A)
Slip	: 1.53 %	Starting method	: Direct On Line
Rated torque	: 183 ft.lb	Approx. weight ³	: 825 lb
Locked rotor torque	: 180 %		
Breakdown torque	: 229 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 8.03 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	92.8	93.0	93.6	93.6	Max. traction	: 864 lb
Power Factor	0.60	0.80	0.86	0.88	Max. compression	: 1689 lb

	Drive end	Non drive end
Bearing type	: 6314 C3	: 6212 Z C3
Sealing	: Without Bearing Seal	: Without Bearing Seal
Lubrication interval	: 14418 h	: 20000 h
Lubricant amount	: 27 g	: 13 g
Lubricant type	Mobil Polyrex EM	

Notes
downloaded from <http://dealerselectric.com>

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	15/04/2019			

Page 1 / 2
Revision


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : Dealers Industrial Equipment 800-469-3110
Customer reference : 12536OP3HFP404TS-W40

Product line : W40 High Efficiency Three-Phase Product code : 14282771
Catalog # : 12536OP3HFP404TS-W40



Performance : 575 V 60 Hz 2P

Rated current : 110 A	Moment of inertia (J) : 8.03 sq.ft.lb
LRC : 6.6	Duty cycle : Cont.(S1)
Rated torque : 183 ft.lb	Insulation class : F
Locked rotor torque : 180 %	Service factor : 1.15
Breakdown torque : 229 %	Temperature rise : 105 K
Rated speed : 3545 rpm	Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		<div>Page 2 / 2</div> <div>Revision</div>		
Checked by				
Date	15/04/2019			

