

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer : Dealers Industrial Equipment 800-469-3110
Customer reference : 06036OP3VFP326TS-W40

Product line : W40 High Efficiency Three-Phase Product code : 14491074
Catalog # : 06036OP3VFP326TS-W40

Frame	: 324/6TS	Locked rotor time	: 30s (cold) 17s (hot)
Output	: 60 HP (45 kW)	Temperature rise	: 105 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 200/400 V	Altitude	: 1000 m.a.s.l.
Rated current	: 162/81.2 A	Protection degree	: IP23
L. R. Amperes	: 958/479 A	Cooling method	: IC01 - ODP
LRC	: 5.9x(Code F)	Mounting	: F-1
No load current	: 46.7/23.3 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3555 rpm	Starting method	: Direct On Line
Slip	: 1.25 %	Approx. weight ³	: 455 lb
Rated torque	: 87.4 ft.lb		
Locked rotor torque	: 180 %		
Breakdown torque	: 200 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 3.41 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads
Efficiency (%)	92.3	92.4	93.0	93.0	Max. traction
Power Factor	0.54	0.78	0.84	0.86	Max. compression

	Drive end	Non drive end
Bearing type	: 6312 Z C3	6211 Z C3
Sealing	: Without Bearing Seal	Without Bearing Seal
Lubrication interval	: 19658 h	20000 h
Lubricant amount	: 21 g	11 g
Lubricant type	Mobil Polyrex EM	

Notes
downloaded from <http://dealerselectric.com>

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	14/04/2019			
			Page	Revision
			1 / 2	


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : Dealers Industrial Equipment 800-469-3110
Customer reference : 06036OP3VFP326TS-W40

Product line : W40 High Efficiency Three-Phase Product code : 14491074
Catalog # : 06036OP3VFP326TS-W40



Performance : 200/400 V 60 Hz 2P

Rated current : 162/81.2 A
LRC : 5.9
Rated torque : 87.4 ft.lb
Locked rotor torque : 180 %
Breakdown torque : 200 %
Rated speed : 3555 rpm

Moment of inertia (J) : 3.41 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 105 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date					

