

CERTIFICATION DATA SHEET

Model#: 48A11T463 E
CONN. DIAGRAM: SEE OULT.
OUTLINE: A-SS74409-400

WINDING#: PE4861108 NONE 2
ASSEMBLY: F1 ONLY

TYPICAL MOTOR PERFORMANCE DATA

HP	KW	SYNC. RPM	F.L. RPM	FRAME	ENCLOSURE	KVA CODE	DESIGN						
1/4	0.19	1200	1075	48Y	TEAO	B	NO DESIGN CODE						
PH	Hz	VOLTS	FL AMPS	START TYPE	DUTY	INSL	S.F	AMB°C	ELEVATION				
1	60	208-230	1.8	ACROSS THE LINE	CONTINUOUS	B3	1.0	40	3300				
FULL LOAD EFF: -		3/4 LOAD EFF: -		1/2 LOAD EFF: -		GTD. EFF		ELEC. TYPE		NO LOAD AMPS			
FULL LOAD PF: -		3/4 LOAD PF: -		1/2 LOAD PF: -		-		PSC 2 SPEED		.4			
F.L. TORQUE		LOCKED ROTOR AMPS		L.R. TORQUE		B.D. TORQUE		F.L. RISE°C					
- LB-FT		2.1		3.09 LB-FT -		- LB-FT -		-					
SOUND PRESSURE @ 3 FT.		SOUND POWER		ROTOR WK^2		MAX. WK^2		SAFE STALL TIME		STARTS /HOUR		APPROX. MOTOR WGT	
- dBA		- dBA		- LB-FT^2		- LB-FT^2		- SEC.		-		- LBS.	

***** SUPPLEMENTAL INFORMATION *****

DE BRACKET TYPE	ODE BRACKET TYPE	MOUNT TYPE	ORIENTATION	SEVERE DUTY	HAZARDOUS LOCATION	DRIP COVER	SCREENS	PAINT
STANDARD	STANDARD	ROUND-EXTENDED STUDS	HORIZONTAL	FALSE	NONE	FALSE	NONE	GRAY (POWDER)

BEARINGS		GREASE	SHAFT TYPE	SPECIAL DE	SPECIAL ODE	SHAFT MATERIAL	FRAME MATERIAL
DE	OPE						
BALL	BALL	MULTEMP SRL	SGL SPL EXT	0.500 x 6.00 WITH 5.50 FULL FLAT	NONE	1144 STRESSPROOF (C-223)	ROLLED STEEL
6203	6203						

THERMO-PROTECTORS				THERMISTORS	CONTROL	SPACE /n HEATERS
THERMOSTATS	PROTECTORS	WDG RTDs	BRG RTDs			
NONE	AUT LCK RTR ONLY	NONE	NONE	NONE	FALSE	NONE VOLTS

*
 N
 O
 T
 E
 S
 *

INVERTER TORQUE: NONE
INV. HP SPEED RANGE: NONE
ENCODER: NONE
NONE NONE
NONE NONE PPR
BRAKE: NONE NONE
NONE P/N NONE
NONE NONE
- FT-LB NONE V NONE Hz