

CERTIFICATION DATA SHEET

Model#: 56B11F5302 L
 CONN. DIAGRAM: A-102006-51
 OUTLINE: A-100246-856

WINDING#: ZB602 NONE 3
 ASSEMBLY: F1 ONLY

TYPICAL MOTOR PERFORMANCE DATA

HP	KW	SYNC. RPM	F.L. RPM	FRAME	ENCLOSURE	KVA CODE	DESIGN
3/4	.56	1200	1140	56C	TEFC	L	N

PH	Hz	VOLTS	FL AMPS	START TYPE	DUTY	INSL	S.F	AMB°C	ELEVATION
1	60	115/208-230	11.4/5.8-5.7	ACROSS THE LINE	CONTINUOUS	B3	1.15/1.0	40	3300

FULL LOAD EFF: 68	3/4 LOAD EFF: 64.8	1/2 LOAD EFF: 58.2	GTD. EFF	ELEC. TYPE	NO LOAD AMPS
FULL LOAD PF: 65.4	3/4 LOAD PF: 55	1/2 LOAD PF: 45.3	0	CAP START CAP RUN	8.7 / 4.4

F.L. TORQUE	LOCKED ROTOR AMPS	L.R. TORQUE	B.D. TORQUE	F.L. RISE°C
54.2 LB-FT	55.4 / 27.7	119 LB-FT 220	124 LB-FT 229	75

SOUND PRESSURE @ 3 FT.	SOUND POWER	ROTOR WK^2	MAX. WK^2	SAFE STALL TIME	STARTS /HOUR	APPROX. MOTOR WGT
- dBA	- dBA	0 LB-FT^2	- LB-FT^2	10 SEC.	-	0 LBS.

*** SUPPLEMENTAL INFORMATION ***

DE BRACKET TYPE	ODE BRACKET TYPE	MOUNT TYPE	ORIENTATION	SEVERE DUTY	HAZARDOUS LOCATION	DRIP COVER	SCREENS	PAINT
C-FACE	BRAKE	BOLT-ON	HORIZONTAL	FALSE	NONE	FALSE	NONE	GRAY (POWDER)

BEARINGS		GREASE	SHAFT TYPE	SPECIAL DE	SPECIAL ODE	SHAFT MATERIAL	FRAME MATERIAL
DE	OPE						
BALL	BALL						
6203	6203	POLYREX EM	STANDARD 56	NONE	NONE	1144 STRESSPROOF (C-223)	ROLLED STEEL

THERMO-PROTECTORS				THERMISTORS	CONTROL	SPACE /n HEATERS
THERMOSTATS	PROTECTORS	WDG RTDs	BRG RTDs			
NONE	NOT	NONE	NONE	NONE	FALSE	NONE VOLTS

* N O T E S *	INVERTER TORQUE: NONE		
	INV. HP SPEED RANGE: NONE		
	ENCODER: NONE		
	NONE NONE		
* N O T E S *	NONE NONE PPR		
	BRAKE: PROVISIONS FOR KIT NONE		
	NONE P/N NONE		
	NONE NONE		
* N O T E S *	NONE FT-LB NONE V NONE Hz		

DATE: 08/13/2016 12:50:44 AM
 FORM 3531 REV.3 02/07/99
 ** Subject to change without notice.