

CERTIFICATION DATA SHEET

Model#: 56T11V5379 A
CONN. DIAGRAM: 005010.01ME
OUTLINE: 028903-625

WINDING#: T63653 NR 3
ASSEMBLY: F1 ONLY

TYPICAL MOTOR PERFORMANCE DATA

| HP | KW | SYNC. RPM | F.L. RPM | FRAME | ENCLOSURE | KVA CODE | DESIGN |
|---------|-----------|-----------|----------|-------|-----------|----------|--------|
| 1/2&1/3 | 0.37&0.25 | 1200 | 1140&940 | 56HC | TENV | K | B |

| PH | Hz | VOLTS | FL AMPS | START TYPE | DUTY | INSL | S.F | AMB°C | ELEVATION |
|----|-------|-----------------------------|------------------------------|---------------------|----------------|------|-----------|-------|-----------|
| 3 | 60/50 | 208- 230/460#190/ 380 | 2.35- 2.3/1.15&1.8/. 9 | LINE OR INVERTER | CONTINUOU S | F4 | 1.15/1.15 | 40 | 3300 |

| FULL LOAD EFF: 77 | 3/4 LOAD EFF: 74.7 | 1/2 LOAD EFF: 70 | GTD. EFF | ELEC. TYPE | NO LOAD AMPS |
|-------------------|--------------------|-------------------|----------|-------------------|--------------|
| FULL LOAD PF: 54 | 3/4 LOAD PF: 49 | 1/2 LOAD PF: 38.1 | 0 | SQ CAGE INV RATED | 1.6 / .8 |

| F.L. TORQUE | LOCKED ROTOR AMPS | L.R. TORQUE | B.D. TORQUE | F.L. RISE°C |
|-------------|-------------------|---------------|---------------|-------------|
| 36 LB-FT | 11.6 / 5.8 | 113 LB-FT 315 | 140 LB-FT 389 | 77 |

| SOUND PRESSURE @ 3 FT. | SOUND POWER | ROTOR WK^2 | MAX. WK^2 | SAFE STALL TIME | STARTS /HOUR | APPROX. MOTOR WGT |
|------------------------|-------------|-------------|-------------|-----------------|--------------|-------------------|
| 0 dBA | 10 dBA | 0.1 LB-FT^2 | 0.1 LB-FT^2 | 10 SEC. | 0 | 0 LBS. |

***** SUPPLEMENTAL INFORMATION *****

| DE BRACKET TYPE | ODE BRACKET TYPE | MOUNT TYPE | ORIENTATION | SEVERE DUTY | HAZARDOUS LOCATION | DRIP COVER | SCREENS | PAINT |
|-----------------|------------------|------------|-------------|-------------|--------------------|------------|---------|----------|
| C-FACE | STANDARD | RIGID | HORIZONTAL | FALSE | NONE | FALSE | NONE | NO PAINT |

| BEARINGS | | GREASE | SHAFT TYPE | SPECIAL DE | SPECIAL ODE | SHAFT MATERIAL | FRAME MATERIAL |
|----------|------|------------|-------------|------------|-------------|-----------------------|-----------------|
| DE | OPE | | | | | | |
| BALL | BALL | POLYREX EM | STANDARD 56 | NONE | NONE | 303 STAINLESS (C-501) | STAINLESS STEEL |
| 6205 | 6205 | | | | | | |

| THERMO-PROTECTORS | | | | THERMISTORS | CONTROL | SPACE /n HEATERS |
|-------------------|------------|----------|----------|-------------|---------|------------------|
| THERMOSTATS | PROTECTORS | WDG RTDs | BRG RTDs | | | |
| NONE | NOT | NONE | NONE | NONE | FALSE | NONE VOLTS |

*
N
O
T
E
S
*

| |
|--|
| INVERTER TORQUE: CONSTANT 3:1 INV. HP SPEED RANGE: NONE |
| ENCODER: NONE NONE NONE NONE NONE PPR |
| BRAKE: NONE NONE NONE P/N NONE NONE NONE - FT-LB NONE V NONE Hz |

DATE: 08/13/2016 12:30:51 AM
 FORM 3531 REV.3 02/07/99
 ** Subject to change without notice.