

CERTIFICATION DATA SHEET

Model#: 56T17W99003 A
CONN. DIAGRAM: 005010.01ME
OUTLINE: 607-0006ME-450

WINDING#: T634201 FR 3
ASSEMBLY: F1 ONLY

TYPICAL MOTOR PERFORMANCE DATA

| HP | KW | SYNC. RPM | F.L. RPM | FRAME | ENCLOSURE | KVA CODE | DESIGN |
|---------|-----------|-----------|-----------|-------|-----------|----------|--------|
| 1/3&1/4 | 0.25&0.19 | 1800 | 1725&1425 | 56C | TEFC | L | B |

| PH | Hz | VOLTS | FL AMPS | START TYPE | DUTY | INSL | S.F | AMB°C | ELEVATION |
|----|-------|-----------------------------|----------------|--------------------|----------------|------|-----------|-------|-----------|
| 3 | 60/50 | 208- 230/460#190/ 380 | 1.7/.85&1.6/.8 | ACROSS THE LINE | CONTINUOU S | F4 | 1.15/1.15 | 40 | 3300 |

| FULL LOAD EFF: 68 | 3/4 LOAD EFF: 59.8 | 1/2 LOAD EFF: 51.5 | GTD. EFF | ELEC. TYPE | NO LOAD AMPS |
|-------------------|--------------------|--------------------|----------|-----------------|--------------|
| FULL LOAD PF: 54 | 3/4 LOAD PF: 50.3 | 1/2 LOAD PF: 39.6 | 0 | SQ CAGE IND RUN | 1.5 / .8 |

| F.L. TORQUE | LOCKED ROTOR AMPS | L.R. TORQUE | B.D. TORQUE | F.L. RISE°C |
|-------------|-------------------|----------------|--------------|-------------|
| 16 LB-FT | 7.3 / 3.7 | 46.7 LB-FT 292 | 80 LB-FT 500 | 0 |

| SOUND PRESSURE @ 3 FT. | SOUND POWER | ROTOR WK^2 | MAX. WK^2 | SAFE STALL TIME | STARTS /HOUR | APPROX. MOTOR WGT |
|------------------------|-------------|---------------|-----------|-----------------|--------------|-------------------|
| 0 dBA | 10 dBA | 0.036 LB-FT^2 | 0 LB-FT^2 | 10 SEC. | 0 | 0 LBS. |

***** SUPPLEMENTAL INFORMATION *****

| DE BRACKET TYPE | ODE BRACKET TYPE | MOUNT TYPE | ORIENTATION | SEVERE DUTY | HAZARDOUS LOCATION | DRIP COVER | SCREENS | PAINT |
|-----------------|------------------|------------|-------------|-------------|--------------------|------------|---------|------------------------------|
| C-FACE | STANDARD | ROUND | HORIZONTAL | FALSE | NONE | FALSE | NONE | WHITE - LEESON (EPOXY) |

| BEARINGS | | GREASE | SHAFT TYPE | SPECIAL DE | SPECIAL ODE | SHAFT MATERIAL | FRAME MATERIAL |
|----------|------|------------|-------------|------------|-------------|--------------------------|----------------|
| DE | OPE | | | | | | |
| BALL | BALL | POLYREX EM | STANDARD 56 | NONE | NONE | 303 STAINLESS (C-501) | ROLLED STEEL |
| 6205 | 6203 | | | | | | |

| THERMO-PROTECTORS | | | | THERMISTORS | CONTROL | SPACE /n HEATERS |
|-------------------|------------|----------|----------|-------------|---------|------------------|
| THERMOSTATS | PROTECTORS | WDG RTDs | BRG RTDs | | | |
| NONE | NOT | NONE | NONE | NONE | FALSE | NONE VOLTS |

*
N
O
T
E
S
*

| |
|---------------------------|
| INVERTER TORQUE: NONE |
| INV. HP SPEED RANGE: NONE |
| ENCODER: NONE |
| NONE NONE |
| NONE NONE PPR |
| BRAKE: NONE NONE |
| NONE P/N NONE |
| NONE NONE |
| - FT-LB NONE V NONE Hz |