

**CERTIFICATION DATA SHEET**

**Model#:** 56T34D5366 D  
**CONN. DIAGRAM:** A-EE7308  
**OUTLINE:** A-100818-656

**WINDING#:** ZT204 DR 3  
**ASSEMBLY:** F1 ONLY

**TYPICAL MOTOR PERFORMANCE DATA**

HP	KW	SYNC. RPM	F.L. RPM	FRAME	ENCLOSURE	KVA CODE	DESIGN
1&3/4	.75&.56	3600	3450&2850	56J	DP	M	B

PH	Hz	VOLTS	FL AMPS	START TYPE	DUTY	INSL	S.F	AMB°C	ELEVATION
3	60/50	208- 230/460#190/ 380	3.7- 3.7/1.85&3.4/1 .7	ACROSS THE LINE	CONTINUOU S	B3	1.4/1.4	40	3300

FULL LOAD EFF: 74&75.5	3/4 LOAD EFF: 69.3	1/2 LOAD EFF: 61.3	GTD. EFF	ELEC. TYPE	NO LOAD AMPS
FULL LOAD PF: 71.3&70	3/4 LOAD PF: 65.5	1/2 LOAD PF: 55.5	70	SQ CAGE IND RUN	2.2 / 1.1

F.L. TORQUE	LOCKED ROTOR AMPS	L.R. TORQUE	B.D. TORQUE	F.L. RISE°C
1.5 LB-FT	29.6 / 14.8	5 LB-FT 333	7 LB-FT 467	38

SOUND PRESSURE @ 3 FT.	SOUND POWER	ROTOR WK^2	MAX. WK^2	SAFE STALL TIME	STARTS /HOUR	APPROX. MOTOR WGT
68 dBA	78 dBA	0.03 LB-FT^2	2 LB-FT^2	12 SEC.	2	24 LBS.

**\*\*\* SUPPLEMENTAL INFORMATION \*\*\***

DE BRACKET TYPE	ODE BRACKET TYPE	MOUNT TYPE	ORIENTATION	SEVERE DUTY	HAZARDOUS LOCATION	DRIP COVER	SCREENS	PAINT
C-FACE	STANDARD	RIGID	HORIZONTAL OR SHAFT DOWN	FALSE	NONE	TRUE	NONE	GRAY (POWDER)

BEARINGS		GREASE	SHAFT TYPE	SPECIAL DE	SPECIAL ODE	SHAFT MATERIAL	FRAME MATERIAL
DE	OPE						
BALL	BALL	POLYREX EM	JET PUMP	NONE	NONE	416 STAINLESS (C-503)	ROLLED STEEL
6203	6203						

THERMO-PROTECTORS				THERMISTORS	CONTROL	SPACE /n HEATERS
THERMOSTATS	PROTECTORS	WDG RTDs	BRG RTDs			
NONE	NOT	NONE	NONE	NONE	FALSE	NONE VOLTS

\*  
N  
O  
T  
E  
S  
\*

INVERTER TORQUE: NONE
INV. HP SPEED RANGE: NONE
ENCODER: NONE
NONE NONE
NONE NONE PPR
BRAKE: NONE NONE
NONE P/N NONE
NONE NONE
NONE FT-LB NONE V NONE Hz

DATE: 08/13/2016 01:18:21 AM  
 FORM 3531 REV.3 02/07/99

\*\* Subject to change without notice.