

**CERTIFICATION DATA SHEET**

**Model#:** 213TTDC6026 AA  
**CONN. DIAGRAM:** 005010-19ME  
**OUTLINE:** 16954960ME

**WINDING#:** T10704007 NONE 3  
**ASSEMBLY:** F1 ONLY

**TYPICAL MOTOR PERFORMANCE DATA**

HP	KW	SYNC. RPM	F.L. RPM	FRAME	ENCLOSURE	KVA CODE	DESIGN
7 1/2&7 1/2	5.6&5.6	1800	1760&1465	213T	DP	J	B

PH	Hz	VOLTS	FL AMPS	START TYPE	DUTY	INSL	S.F	AMB°C	ELEVATION
3	60/50	208- 230/460#200/ 400	20.6- 19.8/9.9&22.2/ 11.1	ACROSS THE LINE	CONTINUOU S	F5	1.15/1.0	40	3300

FULL LOAD EFF: 91&89.5	3/4 LOAD EFF: 91	1/2 LOAD EFF: 90	GTD. EFF	ELEC. TYPE	NO LOAD AMPS
FULL LOAD PF: 78&81	3/4 LOAD PF: 71	1/2 LOAD PF: 59	90.2	SQ CAGE IND RUN	10.6 / 5.3

F.L. TORQUE	LOCKED ROTOR AMPS	L.R. TORQUE	B.D. TORQUE	F.L. RISE°C
22.5 LB-FT	127 / 63.5	45 LB-FT 200	58 LB-FT 258	30

SOUND PRESSURE @ 3 FT.	SOUND POWER	ROTOR WK^2	MAX. WK^2	SAFE STALL TIME	STARTS /HOUR	APPROX. MOTOR WGT
72 dBA	82 dBA	- LB-FT^2	- LB-FT^2	15 SEC.	2	160 LBS.

**\*\*\* SUPPLEMENTAL INFORMATION \*\*\***

DE BRACKET TYPE	ODE BRACKET TYPE	MOUNT TYPE	ORIENTATION	SEVERE DUTY	HAZARDOUS LOCATION	DRIP COVER	SCREENS	PAINT
STANDARD	STANDARD	RIGID	HORIZONTAL	FALSE	NONE	FALSE	NONE	BLUE (ENAMEL)

BEARINGS		GREASE	SHAFT TYPE	SPECIAL DE	SPECIAL ODE	SHAFT MATERIAL	FRAME MATERIAL
DE	OPE						
BALL	BALL	POLYREX EM	T	NONE	NONE	1045 HOT ROLLED (C-204)	CAST IRON
6308	6208						

THERMO-PROTECTORS				THERMISTORS	CONTROL	SPACE /n HEATERS
THERMOSTATS	PROTECTORS	WDG RTDs	BRG RTDs			
NONE	NOT	NONE	NONE	NONE	FALSE	NONE VOLTS

\*  
N  
O  
T  
E  
S  
\*

INVERTER TORQUE: NONE
INV. HP SPEED RANGE: NONE
ENCODER: NONE
NONE NONE
NONE NONE PPR
BRAKE: NONE NONE
NONE P/N NONE
NONE NONE
NONE FT-LB NONE V NONE Hz

DATE: 08/13/2016 10:16:42 AM  
 FORM 3531 REV.3 02/07/99  
 \*\* Subject to change without notice.