

CERTIFICATION DATA SHEET

Model#: 215TTFC6027 AA
CONN. DIAGRAM: 005010.01ME
OUTLINE: 169536.60ME

WINDING#: T10704006 NONE 3
ASSEMBLY: F1/F2 CAPABLE

TYPICAL MOTOR PERFORMANCE DATA

| HP | KW | SYNC. RPM | F.L. RPM | FRAME | ENCLOSURE | KVA CODE | DESIGN |
|----------|---------|-----------|-----------|-------|-----------|----------|--------|
| 10&7 1/2 | 7.5&5.6 | 1800 | 1760&1465 | 215T | TEFC | H | B |

| PH | Hz | VOLTS | FL AMPS | START TYPE | DUTY | INSL | S.F | AMB°C | ELEVATION |
|----|-------|-----------------------------|----------------------------|--------------------|----------------|------|-----------|-------|-----------|
| 3 | 60/50 | 208- 230/460#190/ 380 | 27- 25/12.5&23/11 .5 | ACROSS THE LINE | CONTINUOU S | F2 | 1.15/1.15 | 40 | 3300 |

| FULL LOAD EFF: 91.7&91 | 3/4 LOAD EFF: 91.7 | 1/2 LOAD EFF: 91 | GTD. EFF | ELEC. TYPE | NO LOAD AMPS |
|---------------------------|--------------------|-------------------|----------|-----------------|--------------|
| FULL LOAD PF: 81.6&81 | 3/4 LOAD PF: 75 | 1/2 LOAD PF: 63.5 | 91 | SQ CAGE IND RUN | 11.8 / 5.9 |

| F.L. TORQUE | LOCKED ROTOR AMPS | L.R. TORQUE | B.D. TORQUE | F.L. RISE°C |
|-------------|-------------------|----------------|---------------|-------------|
| 29.8 LB-FT | 162 / 81 | 64.5 LB-FT 216 | 109 LB-FT 365 | 50 |

| SOUND PRESSURE @ 3 FT. | SOUND POWER | ROTOR WK^2 | MAX. WK^2 | SAFE STALL TIME | STARTS /HOUR | APPROX. MOTOR WGT |
|---------------------------|-------------|--------------|-----------|-----------------|-----------------|----------------------|
| 80 dBA | 90 dBA | 1.04 LB-FT^2 | - LB-FT^2 | 15 SEC. | 2 | 177 LBS. |

***** SUPPLEMENTAL INFORMATION *****

| DE BRACKET TYPE | ODE BRACKET TYPE | MOUNT TYPE | ORIENTATION | SEVERE DUTY | HAZARDOUS LOCATION | DRIP COVER | SCREENS | PAINT |
|--------------------|---------------------|---------------|-------------|----------------|-----------------------|---------------|---------|------------------|
| STANDARD | STANDARD | RIGID | HORIZONTAL | FALSE | NONE | FALSE | NONE | BLUE (ENAMEL) |

| BEARINGS | | GREASE | SHAFT TYPE | SPECIAL DE | SPECIAL ODE | SHAFT MATERIAL | FRAME MATERIAL |
|----------|------|------------|------------|------------|-------------|----------------------------|-------------------|
| DE | OPE | | | | | | |
| BALL | BALL | POLYREX EM | T | NONE | NONE | 1045 HOT ROLLED (C-204) | CAST IRON |
| 6308 | 6306 | | | | | | |

| THERMO-PROTECTORS | | | | THERMISTORS | CONTROL | SPACE /n HEATERS |
|-------------------|------------|----------|----------|-------------|---------|------------------|
| THERMOSTATS | PROTECTORS | WDG RTDs | BRG RTDs | | | |
| NONE | NOT | NONE | NONE | NONE | FALSE | NONE VOLTS |

*
N
O
T
E
S
*

| |
|---------------------------|
| INVERTER TORQUE: NONE |
| INV. HP SPEED RANGE: NONE |
| ENCODER: NONE |
| NONE NONE |
| NONE NONE PPR |
| BRAKE: NONE NONE |
| NONE P/N NONE |
| NONE NONE |
| - FT-LB NONE V NONE Hz |