

**CERTIFICATION DATA SHEET**

**Model#:** 256THFNA19081 AB  
**CONN. DIAGRAM:** A-EE7300  
**OUTLINE:** B-SS203002-1225

**WINDING#:** 256674 NONE 8  
**ASSEMBLY:** F1/F2 CAPABLE

**TYPICAL MOTOR PERFORMANCE DATA**

| HP | KW  | SYNC. RPM | F.L. RPM | FRAME | ENCLOSURE | KVA CODE | DESIGN |
|----|-----|-----------|----------|-------|-----------|----------|--------|
| 10 | 7.5 | 1200      | 1176     | 256T  | TEFC      | H        | B      |

| PH | Hz | VOLTS | FL AMPS | START TYPE          | DUTY           | INSL | S.F  | AMB°C | ELEVATION |
|----|----|-------|---------|---------------------|----------------|------|------|-------|-----------|
| 3  | 60 | 575   | 10.5    | LINE OR<br>INVERTER | CONTINUOU<br>S | F3   | 1.15 | 40    | 3300      |

| FULL LOAD EFF: 91 | 3/4 LOAD EFF: 91  | 1/2 LOAD EFF: 90.2 | GTD. EFF | ELEC. TYPE        | NO LOAD AMPS |
|-------------------|-------------------|--------------------|----------|-------------------|--------------|
| FULL LOAD PF: 79  | 3/4 LOAD PF: 72.5 | 1/2 LOAD PF: 61    | 90.2     | SQ CAGE INV RATED | 5.2          |

| F.L. TORQUE | LOCKED ROTOR AMPS | L.R. TORQUE  | B.D. TORQUE   | F.L. RISE°C |
|-------------|-------------------|--------------|---------------|-------------|
| 44.7 LB-FT  | 64.8              | 92 LB-FT 206 | 139 LB-FT 311 | 40          |

| SOUND PRESSURE @ 3 FT. | SOUND POWER | ROTOR WK^2 | MAX. WK^2   | SAFE STALL TIME | STARTS /HOUR | APPROX. MOTOR WGT |
|------------------------|-------------|------------|-------------|-----------------|--------------|-------------------|
| 56 dBA                 | 66 dBA      | 3 LB-FT^2  | 225 LB-FT^2 | 20 SEC.         | 2            | 390 LBS.          |

**\*\*\* SUPPLEMENTAL INFORMATION \*\*\***

| DE BRACKET TYPE | ODE BRACKET TYPE | MOUNT TYPE | ORIENTATION | SEVERE DUTY            | HAZARDOUS LOCATION | DRIP COVER | SCREENS | PAINT        |
|-----------------|------------------|------------|-------------|------------------------|--------------------|------------|---------|--------------|
| STANDARD        | STANDARD         | RIGID      | HORIZONTAL  | PREMIUM<br>SEVERE DUTY | DIVISION 2 T2B     | FALSE      | NONE    | BLUE (EPOXY) |

| BEARINGS |      | GREASE     | SHAFT TYPE | SPECIAL DE | SPECIAL ODE | SHAFT MATERIAL             | FRAME MATERIAL |
|----------|------|------------|------------|------------|-------------|----------------------------|----------------|
| DE       | OPE  |            |            |            |             |                            |                |
| BALL     | BALL | POLYREX EM | T          | NONE       | NONE        | 1045 HOT<br>ROLLED (C-204) | CAST IRON      |
| 6309     | 6210 |            |            |            |             |                            |                |

| THERMO-PROTECTORS |            |          |          | THERMISTORS | CONTROL | SPACE /n HEATERS |
|-------------------|------------|----------|----------|-------------|---------|------------------|
| THERMOSTATS       | PROTECTORS | WDG RTDs | BRG RTDs |             |         |                  |
| NONE              | NOT        | NONE     | NONE     | NONE        | FALSE   | NONE VOLTS       |

\*  
N  
O  
T  
E  
S  
\*

|   |
|---|
| INVERTER TORQUE: CONSTANT 2:1<br>INV. HP SPEED RANGE: NONE                  |
| ENCODER: NONE<br>NONE NONE<br>NONE NONE PPR                                 |
| BRAKE: NONE NONE<br>NONE P/N NONE<br>NONE NONE<br>NONE FT-LB NONE V NONE Hz |

DATE: 08/13/2016 10:24:41 AM  
 FORM 3531 REV.3 02/07/99  
 \*\* Subject to change without notice.