

**CERTIFICATION DATA SHEET**

**Model#:** 256TTFCA6095 AA  
**CONN. DIAGRAM:** EE7300  
**OUTLINE:** SS620567

**WINDING#:** CHT25660001 NONE 3  
**ASSEMBLY:** F1/F2 CAPABLE

**TYPICAL MOTOR PERFORMANCE DATA**

| HP | KW   | SYNC. RPM | F.L. RPM | FRAME | ENCLOSURE | KVA CODE | DESIGN |
|----|------|-----------|----------|-------|-----------|----------|--------|
| 10 | 7.50 | 1200      | 1180     | 256JP | TEFC      | G        | B      |

| PH | Hz | VOLTS | FL AMPS | START TYPE       | DUTY       | INSL | S.F  | AMB°C | ELEVATION |
|----|----|-------|---------|------------------|------------|------|------|-------|-----------|
| 3  | 60 | 575   | 11.2    | LINE OR INVERTER | CONTINUOUS | F7   | 1.15 | 40    | 3300      |

| FULL LOAD EFF: 91 | 3/4 LOAD EFF: 91 | 1/2 LOAD EFF: 90.2 | GTD. EFF | ELEC. TYPE        | NO LOAD AMPS |
|-------------------|------------------|--------------------|----------|-------------------|--------------|
| FULL LOAD PF: 74  | 3/4 LOAD PF: 68  | 1/2 LOAD PF: 56    | 90.2     | SQ CAGE INV RATED | 5.6          |

| F.L. TORQUE | LOCKED ROTOR AMPS | L.R. TORQUE  | B.D. TORQUE   | F.L. RISE°C |
|-------------|-------------------|--------------|---------------|-------------|
| 44.5 LB-FT  | 60                | 69 LB-FT 155 | 130 LB-FT 292 | 45          |

| SOUND PRESSURE @ 3 FT. | SOUND POWER | ROTOR WK^2 | MAX. WK^2   | SAFE STALL TIME | STARTS /HOUR | APPROX. MOTOR WGT |
|------------------------|-------------|------------|-------------|-----------------|--------------|-------------------|
| 56 dBA                 | 66 dBA      | 3 LB-FT^2  | 200 LB-FT^2 | 20 SEC.         | 2            | 375 LBS.          |

**\*\*\* SUPPLEMENTAL INFORMATION \*\*\***

| DE BRACKET TYPE | ODE BRACKET TYPE | MOUNT TYPE | ORIENTATION              | SEVERE DUTY | HAZARDOUS LOCATION | DRIP COVER | SCREENS | PAINT         |
|-----------------|------------------|------------|--------------------------|-------------|--------------------|------------|---------|---------------|
| C-FACE          | STANDARD         | RIGID      | HORIZONTAL OR SHAFT DOWN | FALSE       | NONE               | FALSE      | NONE    | BLUE (ENAMEL) |

| BEARINGS |      | GREASE     | SHAFT TYPE | SPECIAL DE | SPECIAL ODE | SHAFT MATERIAL          | FRAME MATERIAL |
|----------|------|------------|------------|------------|-------------|-------------------------|----------------|
| DE       | OPE  |            |            |            |             |                         |                |
| BALL     | BALL | POLYREX EM | JP         | NONE       | NONE        | 1045 HOT ROLLED (C-204) | CAST IRON      |
| 6309     | 6209 |            |            |            |             |                         |                |

| THERMO-PROTECTORS |            |          |          | THERMISTORS | CONTROL | SPACE /n HEATERS |
|-------------------|------------|----------|----------|-------------|---------|------------------|
| THERMOSTATS       | PROTECTORS | WDG RTDs | BRG RTDs |             |         |                  |
| NONE              | NOT        | NONE     | NONE     | NONE        | FALSE   | NONE VOLTS       |

\*  
N  
O  
T  
E  
S  
\*

|                                |
|--------------------------------|
| INVERTER TORQUE: VARIABLE 10:1 |
| INV. HP SPEED RANGE: NONE      |
| ENCODER: NONE                  |
| NONE NONE                      |
| NONE NONE PPR                  |
| BRAKE: NONE NONE               |
| NONE P/N NONE                  |
| NONE NONE                      |
| NONE FT-LB NONE V NONE Hz      |

DATE: 08/13/2016 10:23:45 AM  
 FORM 3531 REV.3 02/07/99  
 \*\* Subject to change without notice.