

CERTIFICATION DATA SHEET

Model#: 286TTFCA6013 AA
CONN. DIAGRAM: EE7300
OUTLINE: SS620568

WINDING#: CHT28620004 NONE 3
ASSEMBLY: F1/F2 CAPABLE

TYPICAL MOTOR PERFORMANCE DATA

| HP | KW | SYNC. RPM | F.L. RPM | FRAME | ENCLOSURE | KVA CODE | DESIGN |
|----|------|-----------|----------|-------|-----------|----------|--------|
| 30 | 22.4 | 3600 | 3555 | 286JP | TEFC | G | B |

| PH | Hz | VOLTS | FL AMPS | START TYPE | DUTY | INSL | S.F | AMB°C | ELEVATION |
|----|----|-------|---------|------------------|------------|------|------|-------|-----------|
| 3 | 60 | 575 | 27.2 | LINE OR INVERTER | CONTINUOUS | F7 | 1.15 | 40 | 3300 |

| FULL LOAD EFF: 92.4 | 3/4 LOAD EFF: 91.7 | 1/2 LOAD EFF: 91.7 | GTD. EFF | ELEC. TYPE | NO LOAD AMPS |
|---------------------|--------------------|--------------------|----------|-------------------|--------------|
| FULL LOAD PF: 90 | 3/4 LOAD PF: 88 | 1/2 LOAD PF: 82 | 91.7 | SQ CAGE INV RATED | 7.2 |

| F.L. TORQUE | LOCKED ROTOR AMPS | L.R. TORQUE | B.D. TORQUE | F.L. RISE°C |
|-------------|-------------------|--------------|---------------|-------------|
| 44 LB-FT | 168 | 78 LB-FT 177 | 110 LB-FT 250 | 60 |

| SOUND PRESSURE @ 3 FT. | SOUND POWER | ROTOR WK^2 | MAX. WK^2 | SAFE STALL TIME | STARTS /HOUR | APPROX. MOTOR WGT |
|------------------------|-------------|------------|------------|-----------------|--------------|-------------------|
| 72 dBA | 82 dBA | 3 LB-FT^2 | 35 LB-FT^2 | 20 SEC. | 2 | 500 LBS. |

***** SUPPLEMENTAL INFORMATION *****

| DE BRACKET TYPE | ODE BRACKET TYPE | MOUNT TYPE | ORIENTATION | SEVERE DUTY | HAZARDOUS LOCATION | DRIP COVER | SCREENS | PAINT |
|-----------------|------------------|------------|-------------|-------------|--------------------|------------|---------|---------------|
| C-FACE | STANDARD | RIGID | HORIZONTAL | FALSE | NONE | FALSE | NONE | BLUE (ENAMEL) |

| BEARINGS | | GREASE | SHAFT TYPE | SPECIAL DE | SPECIAL ODE | SHAFT MATERIAL | FRAME MATERIAL |
|----------|------|------------|------------|------------|-------------|-------------------------|----------------|
| DE | OPE | | | | | | |
| BALL | BALL | POLYREX EM | JP | NONE | NONE | 1045 HOT ROLLED (C-204) | CAST IRON |
| 6211 | 6211 | | | | | | |

| THERMO-PROTECTORS | | | | THERMISTORS | CONTROL | SPACE /n HEATERS |
|-------------------|------------|----------|----------|-------------|---------|------------------|
| THERMOSTATS | PROTECTORS | WDG RTDs | BRG RTDs | | | |
| NONE | NOT | NONE | NONE | NONE | FALSE | NONE VOLTS |

*
N
O
T
E
S
*

| |
|---|
| INVERTER TORQUE: VARIABLE 10:1 INV. HP SPEED RANGE: NONE |
| ENCODER: NONE NONE NONE NONE NONE PPR |
| BRAKE: NONE NONE NONE P/N NONE NONE NONE NONE FT-LB NONE V NONE Hz |

DATE: 08/13/2016 10:54:50 AM
 FORM 3531 REV.3 02/07/99
 ** Subject to change without notice.