

CERTIFICATION DATA SHEET

Model#: 324TTFS16066 AN
CONN. DIAGRAM: A-EE7308
OUTLINE: B-SS28289-1300

WINDING#: K3244127 NONE 1
ASSEMBLY: F1/F2 CAPABLE

TYPICAL MOTOR PERFORMANCE DATA

| HP | KW | SYNC. RPM | F.L. RPM | FRAME | ENCLOSURE | KVA CODE | DESIGN |
|----|----|-----------|----------|-------|-----------|----------|--------|
| 40 | 30 | 1800 | 1780 | 324T | TEFC | G | B |

| PH | Hz | VOLTS | FL AMPS | START TYPE | DUTY | INSL | S.F | AMB°C | ELEVATION |
|----|----|---------|---------|------------------|------------|------|------|-------|-----------|
| 3 | 60 | 230/460 | 95/47.5 | LINE OR INVERTER | CONTINUOUS | F3 | 1.15 | 40 | 3300 |

| FULL LOAD EFF: 94.1 | 3/4 LOAD EFF: 94.5 | 1/2 LOAD EFF: 94.5 | GTD. EFF | ELEC. TYPE | NO LOAD AMPS |
|---------------------|--------------------|--------------------|----------|-------------------|--------------|
| FULL LOAD PF: 83 | 3/4 LOAD PF: 79.5 | 1/2 LOAD PF: 71 | 93.6 | SQ CAGE INV RATED | 35 / 17.5 |

| F.L. TORQUE | LOCKED ROTOR AMPS | L.R. TORQUE | B.D. TORQUE | F.L. RISE°C |
|-------------|-------------------|---------------|---------------|-------------|
| 118 LB-FT | 580 / 290 | 218 LB-FT 185 | 305 LB-FT 258 | 65 |

| SOUND PRESSURE @ 3 FT. | SOUND POWER | ROTOR WK^2 | MAX. WK^2 | SAFE STALL TIME | STARTS /HOUR | APPROX. MOTOR WGT |
|------------------------|-------------|-------------|-------------|-----------------|--------------|-------------------|
| 65 dBA | 75 dBA | 8.8 LB-FT^2 | 275 LB-FT^2 | 25 SEC. | 2 | 700 LBS. |

***** SUPPLEMENTAL INFORMATION *****

| DE BRACKET TYPE | ODE BRACKET TYPE | MOUNT TYPE | ORIENTATION | SEVERE DUTY | HAZARDOUS LOCATION | DRIP COVER | SCREENS | PAINT |
|-----------------|------------------|------------|-------------|-------------|--------------------|------------|---------|---------------|
| STANDARD | STANDARD | RIGID | HORIZONTAL | FALSE | NONE | FALSE | NONE | BLUE (ENAMEL) |

| BEARINGS | | GREASE | SHAFT TYPE | SPECIAL DE | SPECIAL ODE | SHAFT MATERIAL | FRAME MATERIAL |
|----------|------|------------|------------|------------|-------------|-------------------------|----------------|
| DE | OPE | | | | | | |
| BALL | BALL | POLYREX EM | T | NONE | NONE | 1045 HOT ROLLED (C-204) | CAST IRON |
| 6312 | 6311 | | | | | | |

| THERMO-PROTECTORS | | | | THERMISTORS | CONTROL | SPACE /n HEATERS |
|-------------------|------------|----------|----------|-------------|---------|------------------|
| THERMOSTATS | PROTECTORS | WDG RTDs | BRG RTDs | | | |
| NONE | NOT | NONE | NONE | NONE | FALSE | NONE VOLTS |

*
N
O
T
E
S
*

| |
|--|
| INVERTER TORQUE: CONSTANT 20:1 INV. HP SPEED RANGE: 1.5 X BASE SPEED |
| ENCODER: NONE NONE NONE NONE NONE PPR |
| BRAKE: NONE NONE NONE P/N NONE NONE NONE - FT-LB NONE V NONE Hz |

DATE: 08/13/2016 02:36:24 PM
 FORM 3531 REV.3 02/07/99
 ** Subject to change without notice.