

CERTIFICATION DATA SHEET

Model#: 365TTFS6040 EV
CONN. DIAGRAM: A-EE7300U
OUTLINE: B-SS504688-1450

WINDING#: T367405 NONE 2
ASSEMBLY: F1/F2 CAPABLE

TYPICAL MOTOR PERFORMANCE DATA

| HP | KW | SYNC. RPM | F.L. RPM | FRAME | ENCLOSURE | KVA CODE | DESIGN |
|----|----|-----------|----------|-------|-----------|----------|--------|
| 75 | 56 | 1800 | 1780 | 365T | TEFC | G | B |

| PH | Hz | VOLTS | FL AMPS | START TYPE | DUTY | INSL | S.F | AMB°C | ELEVATION |
|----|----|-------|---------|-----------------|------------|------|------|-------|-----------|
| 3 | 60 | 575 | 69 | ACROSS THE LINE | CONTINUOUS | F1 | 1.15 | 40 | 3300 |

| FULL LOAD EFF: 95.4 | 3/4 LOAD EFF: 95.4 | 1/2 LOAD EFF: 95 | GTD. EFF | ELEC. TYPE | NO LOAD AMPS |
|---------------------|--------------------|------------------|----------|-----------------|--------------|
| FULL LOAD PF: 86 | 3/4 LOAD PF: 83.5 | 1/2 LOAD PF: 76 | 95 | SQ CAGE IND RUN | 22.4 |

| F.L. TORQUE | LOCKED ROTOR AMPS | L.R. TORQUE | B.D. TORQUE | F.L. RISE°C |
|-------------|-------------------|---------------|---------------|-------------|
| 221 LB-FT | 433.6 | 445 LB-FT 201 | 575 LB-FT 260 | 80 |

| SOUND PRESSURE @ 3 FT. | SOUND POWER | ROTOR WK^2 | MAX. WK^2 | SAFE STALL TIME | STARTS /HOUR | APPROX. MOTOR WGT |
|------------------------|-------------|--------------|-------------|-----------------|--------------|-------------------|
| 68 dBA | 78 dBA | 18.5 LB-FT^2 | 500 LB-FT^2 | 25 SEC. | 2 | 1050 LBS. |

***** SUPPLEMENTAL INFORMATION *****

| DE BRACKET TYPE | ODE BRACKET TYPE | MOUNT TYPE | ORIENTATION | SEVERE DUTY | HAZARDOUS LOCATION | DRIP COVER | SCREENS | PAINT |
|-----------------|------------------|------------|-------------|-------------|--------------------|------------|---------|---------------|
| STANDARD | STANDARD | RIGID | HORIZONTAL | FALSE | NONE | FALSE | NONE | BLUE (ENAMEL) |

| BEARINGS | | GREASE | SHAFT TYPE | SPECIAL DE | SPECIAL ODE | SHAFT MATERIAL | FRAME MATERIAL |
|----------|------|------------|------------|------------|-------------|-------------------------|----------------|
| DE | OPE | | | | | | |
| BALL | BALL | POLYREX EM | T | NONE | NONE | 1045 HOT ROLLED (C-204) | CAST IRON |
| 6314 | 6312 | | | | | | |

| THERMO-PROTECTORS | | | | THERMISTORS | CONTROL | SPACE /n HEATERS |
|-------------------|------------|----------|----------|-------------|---------|------------------|
| THERMOSTATS | PROTECTORS | WDG RTDs | BRG RTDs | | | |
| NONE | NOT | NONE | NONE | NONE | FALSE | NONE VOLTS |

*
N
O
T
E
S
*

| |
|---------------------------|
| INVERTER TORQUE: NONE |
| INV. HP SPEED RANGE: NONE |
| ENCODER: NONE |
| NONE NONE |
| NONE NONE PPR |
| BRAKE: NONE NONE |
| NONE P/N NONE |
| NONE NONE |
| - FT-LB NONE V NONE Hz |

DATE: 08/13/2016 02:50:08 PM
 FORM 3531 REV.3 02/07/99
 ** Subject to change without notice.