



NOTES:

1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
3. NAMEPLATES TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

(B-SS509751)

						TOLERANCES UNLESS SPECIFIED				DRAWN DA 02-06-1991					
						DEC.	INCHES			CHK	TB	02-06-1991			
5 CORRECTED FRAME & C'BOX MU45547						KL	05-13-2003	JES	.X	±.1	APPD ML 02-06-1991				
4 3" NPT WAS Ø2.50 NPT CN 28405						DRS	11-13-2002		.XX	±.03	SCALE 11=64				
3 REV'D CONDUIT BOX GEOMETRY						NJS	02-17-2000		.XXX	±.005	REF (OIL WELL DUTY)				
2 ADDED OVERALL DIMENSIONS CN27400-827						BJW	01-17-2000		.XXXX	±.0005	FMF				
1 NEW DRAWING CN13005						DA	02-06-1991				PREV				
NO. REVISION						BY & DATE		CHK	ANG	±7'30"	FINISH		RFP		
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT								RFP	CAD FILE SS513939		SIZE	DRAWING NO.	PAGE	OF	REV.
DASH	FRAME	B	C	2F	BS			DIST	WA	B	SS513939	5			
1850	444T	17.00	38.06	14.50	7.25										
2050	445T	19.00	40.06	16.50	8.25										