



- NOTES:
1. CONDUIT BOX CAN ONLY BE ROTATED CLOCKWISE UP TO 270° FROM ITS ORIGINAL POSITION.
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
 3. NAMEPLATES TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

DASH	FRAME	B	C	2F	2FF	BS
1275	284TS	12.50	24.97	9.50		4.75
1425	284/86TS	13.00	26.47	9.50	11.00	5.50

		TOLERANCES UNLESS SPECIFIED		MARATHON ELECTRIC		DRAWN DAH 03-28-2001	
		DEC.	INCHES			CHK	ML 03-28-2001
4	UPDATED TO NEW FRAME DESIGN	MU109540	MSG 08-30-2012	BW	.X	±.1	APPD BW 03-28-2001
3	REVISED DRAWING		RJW 04-05-2007		.XX	±.03	SCALE 7=32
2	REDRAWN IN AUTOCAD		TAT 06-29-2004	ML	.XXX	±.005	REF
1	NEW DRAWING	MU36545	DAH 03-28-2001		.XXXX	±.0005	FMF
NO.	REVISION		BY & DATE	CHK	ANG	±7'30"	PREV
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT				RFP	CAD FILE ss311134		SIZE DRAWING NO. PAGE OF REV.
				DIST	B		SS311134 3