



NOTES:

1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

						TOLERANCES UNLESS SPECIFIED				DRAWN DA 02-06-1991	
						DEC.	INCHES			CHK ML 02-06-1991	
3 REDRAWN TO AUTOCAD						KL 03-01-2005	.XX	±.03	TITLE OUTLINE - SPL. LEAD HOLE SIZE 505UZ FR. - DR.PR. - SCREENED		APPD GK 02-06-1991
2 CORRECT KEY LENGTH & RE'VD C'BOX GEO. MU3582						KL 02-26-2001	.XXX	±.005			SCALE 9-64
1 NEW DRAWING CN 13005						DA 02-06-1991	.XXXX	±.0005	MATL		REF (OIL FIELD)
NO. REVISION						BY & DATE	CHK ANG ±7'30"	FINISH			FMF
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT						RFP	CAD FILE SS513940	SIZE B	DRAWING NO. SS513940	PAGE OF 3	
DASH	FRAME	B	C	2F	BS	DIST WA					
2100	505UZ	20.50	45.19	18.00	9.00						