



NOTES:

1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

(B-SS509462)

						TOLERANCES UNLESS SPECIFIED				DRAWN DA 02-06-1991				
						DEC.	INCHES			CHK	TB	02-06-1991		
						.X	±.1			APPD	ML	02-06-1991		
3	UPDATED FRAME AND CONDUIT BOX CN 24390					KL	07-12-2005	.XX	±.03	TITLE OUTLINE - GRD. SCREW - SCREENED				
2	REDRAWN IN AUTOCAD					TAT	06-13-2005	ML	.XXX	±.005	360T FR. - DR.PR. - OIL WELL DUTY			
1	NEW DRAWING CN 13005					DA	02-06-1991	.XXXX	±.0005	MATL	REF			
NO.	REVISION					BY	DATE	CHK	ANG	±7'30"	FINISH	FMF		
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT						RFP		CAD FILE SS513938		SIZE	DRAWING NO.	PAGE	OF	REV.
						DIST	WA			B	SS513938	3		3

DASH	FRAME	B	C	2F	BS
1400	364T	13.25	28.93	11.25	5.62
1500	365T	14.25	29.93	12.25	6.12