



NOTES:

1. BOX CAN BE ROTATED ON ITS AXIS.
2. BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

1050	254TC	26.34	22.59	10.25	8.25	4.12
1225	256TC	28.09	24.34	12.00	10.00	5.00
DASH	FRAME	C	AG	B	2F	BS

			TOLERANCES UNLESS SPECIFIED			DRAWN CAV 12-20-1999	
			DEC.	INCHES		CHK ML 12-21-1999	
5	REDRAWN IN AUTOCAD	TAT 06-24-2005	DRS	.X	±.1	APPD GK 12-21-1999	
4	UPDATED SHAFT COVER ON O.D.E. CN 29100-1577	DRS 03-13-2001		.XX	±.03	SCALE 1=4	
3	REVISED TO NEC CONDUIT BOX CN 28427	NJS 08-28-2000		.XXX	±.005	REF	
2	FRONT EXT. WAS .625 DIA. CN 29100-413	MJD 04-19-2000		.XXXX	±.0005	FMF	
NO.	REVISION	BY & DATE	CHK	ANG	±7'30"	PREV	
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT						RFP	CAD FILE ss203502
						DIST LB	SIZE B DRAWING NO. SS203502 PAGE OF 5 REV.