



- NOTES:  
 1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.  
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.  
 3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

DASH	FRAME	B	C	2F	BS
1275	284T	11.75	23.49	9.50	4.75
1325	284/286T	12.63	24.94	9.50	5.50
1512	286T	14.50	26.81	11.00	6.44

TOLERANCES UNLESS SPECIFIED		MARATHON ELECTRIC		DRAWN R/JW 10-08-2007	
DEC.	INCHES	CHK	ANG	CHK	ML 10-09-2007
.X	±.1	RFP	10-09-2007	APPD	BW 10-09-2007
.XX	±.02	TITLE OUTLINE		SCALE	1=4
.XXX	±.005	280 FR. - TS - DR.PR. - CAST IRON		REF	SS207470
.XXXX	±.0005	MATERIAL		FMF	MUB2155
NO.	REVISION	BY & DATE	FINISH	PREV	
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT				RFP	10-09-2007
				CAD FILE	SS207936
				SIZE	DRAWING NO. PAGE OF REV.
				B	SS207936