TYPE	OUTPUT		POLE	TIME RATING	VOLTAGE V	Hz	SYN.SPEED R.P.M
	HP	KW					
AEJHTK	800	597	8	CONT.	2300/4160	60	900

TOTALLY ENCLOSED FAN COOLED TYPE. SQUIRREL CAGE ROTOR







NOTE:

1. DIMENSIONS IN MM
2. FRAME NO. 450C
3. F CLASS INSULATION
4. FOR DIRECT FLEXIBLE COUPLING
5. WITH SPACE HEATER 120 VOLT SINGLE PHASE 300 WATTS
6. WITH 100 OHM PLATINUM WINDING RTD'S 2/PHASE
7. BEARING SIZE: DRIVE END: 6324
   NON-DRIVE END: 6322
8. MOTOR APPROX. WEIGHT: 4400 KGS

TW-66C

DWN.	W.L.LIN	APR·22·2003
CHKD.	W.L.LIN	APR·22·2003
APPD.	C.WANG	APR·22·2003

DATE MAY 7, 2004
CATALOG NO. JH08008

OUTLINE DIMENSIONS
3-PHASE INDUCTION MOTOR

TECO Westinghouse

DWG NO. 3A040T4070 REV: 00

Downloaded from Dealers Industrial Equipment -- Visit https://DealersElectric.com or call (908) 688-1966 for all of your Teco needs!