

# TECO Westinghouse

ISSUED <b>8/25/2004</b>	<b>PERFORMANCE DATA</b> <b>3-PHASE INDUCTION MOTOR</b>	ENCLOSURE <b>ODP</b>
TYPE <b>ASGAJM</b>		CATALOG# <b>DJM1/54</b>

### NAMEPLATE INFORMATION

OUTPUT		POLE	FRAME SIZE	VOLTS	HZ	RATED AMBIENT	INS. CLASS	NEMA DESIGN	TIME RATING	SERVICE FACTOR
HP	KW									
<b>1.5</b>	<b>1.1</b>	<b>4</b>	<b>145T</b>	<b>230/460</b>	<b>60</b>	<b>40°C</b>	<b>F</b>	<b>B</b>	<b>CONT.</b>	<b>1.15</b>

### TYPICAL PERFORMANCE

FULL LOAD RPM	EFFICIENCY				POWER FACTOR			MAXIMUM POWER FACTOR CORRECTION
	FULL LOAD		3/4 LOAD %	1/2 LOAD %	FULL LOAD %	3/4 LOAD %	1/2 LOAD %	
	MIN%	NOM%						
<b>1735</b>	<b>81.5</b>	<b>84</b>	<b>84</b>	<b>82.2</b>	<b>84</b>	<b>79.2</b>	<b>68.5</b>	<b>1.409 KVAR</b>

### CURRENTS

NO LOAD				FULL LOAD				LOCKED ROTOR				NEMA KVA CODE LETTER
AT 200 VOLT	AT 208 VOLT	AT 230 VOLT	AT 460 VOLT	AT 200 VOLT	AT 208 VOLT	AT 230 VOLT	AT 460 VOLT	AT 200 VOLT	AT 208 VOLT	AT 230 VOLT	AT 460 VOLT	
<b>2.0</b>	<b>2.0</b>	<b>1.8</b>	<b>0.9</b>	<b>4.6</b>	<b>4.6</b>	<b>4.6</b>	<b>2.0</b>	<b>40.3</b>	<b>40.3</b>	<b>40.3</b>	<b>17.5</b>	

### TORQUE

### INERTIA

### ACCEL TIME

FULL LOAD lb-ft	LOCKED ROTOR %FLT	PULL UP %FLT	BREAK DOWN %FLT	ROTOR WR <sup>2</sup> lb-ft <sup>2</sup>	NEMA LOAD WK <sup>2</sup> lb-ft <sup>2</sup>	MAX ALLOWABLE WK <sup>2</sup> lb-ft <sup>2</sup>	NEMA LOAD WK <sup>2</sup> Sec.	MAX ALLOWABLE WK <sup>2</sup> Sec.
<b>4.539</b>	<b>245</b>	<b>205</b>	<b>315</b>	<b>0.132</b>	<b>8.6</b>	<b>19.05</b>	<b>4.24</b>	<b>9.30</b>

SAFE STALL TIME IN SECONDS		ALLOWABLE STARTS PER HOUR		SOUND PRESSURE LEVEL @ 3 FT dB(A)
COLD	HOT	COLD	HOT	
<b>42</b>	<b>29</b>	<b>2</b>	<b>1</b>	<b>55</b>

APPROVED:	<b>M. PRATER</b>	DRAWING NO.	<b>31057DJM1/54</b>	REV. <b>0</b>
-----------	------------------	-------------	---------------------	---------------