

# TECO Westinghouse

ISSUED <b>April 13, 2006</b>	<b>PERFORMANCE DATA</b>	ENCLOSURE <b>TEFC</b>
TYPE <b>AEHH8N</b>	<b>3-PHASE INDUCTION MOTOR</b>	CATALOG# <b>EP5006-50</b>

### NAMEPLATE INFORMATION

OUTPUT		POLE	FRAME SIZE	VOLTAGE	HZ	RATED AMBIENT	INS. CLASS	NEMA DESIGN	TIME RATING	SERVICE FACTOR
HP	KW									
<b>500</b>	<b>373.0</b>	<b>6</b>	<b>5808B</b>	<b>380</b>	<b>50</b>	<b>40°C</b>	<b>F</b>	<b>B</b>	<b>CONT.</b>	<b>1.00</b>

### TYPICAL PERFORMANCE

FULL LOAD RPM	EFFICIENCY				POWER FACTOR			MAXIMUM POWER FACTOR CORRECTION
	FULL LOAD		3/4 LOAD %	1/2 LOAD %	F. L. %	3/4 LOAD %	1/2 LOAD %	
	MIN. %	NOM. %						
<b>987</b>	<b>94.6</b>	<b>95.4</b>	<b>95</b>	<b>93.2</b>	<b>87.8</b>	<b>85.8</b>	<b>81.8</b>	<b>94 KVAR</b>

### CURRENTS

NO LOAD	FULL LOAD	LOCKED ROTOR	NEMA KVA CODE LETTER
AT	AT	AT	
380 VOLT	380 VOLT	380 VOLT	
<b>118.00</b>	<b>677.00</b>	<b>3625.00</b>	
			<b>G</b>

### TORQUE

### INERTIA

### ACCEL TIME

FULL LOAD lb-ft	LOCKED ROTOR %FLT	PULL UP %FLT	BREAK DOWN %FLT	ROTOR	NEMA	MAX	NEMA	MAX
				WR <sup>2</sup> lb-ft <sup>2</sup>	LOAD WK <sup>2</sup> lb-ft <sup>2</sup>	ALLOWABLE WK <sup>2</sup> lb-ft <sup>2</sup>	LOAD WK <sup>2</sup> Sec	ALLOWABLE WK <sup>2</sup> Sec
<b>2660</b>	<b>76</b>	<b>76</b>	<b>168</b>	<b>473</b>	<b>8029</b>	<b>16058</b>	<b>8.13</b>	<b>15.81</b>

SAFE STALL TIME IN SECONDS

ALLOWABLE STARTS PER HOUR

SOUND PRESSURE LEVEL @ 3 FT dB(A)

COLD	HOT	COLD	HOT	83
<b>24</b>	<b>17</b>	<b>2</b>	<b>1</b>	

APPROVED:	<b>M. PRATER</b>	DRAWING NO.	<b>31057EP5006</b>	REVISION <b>0</b>
-----------	------------------	-------------	--------------------	-------------------