TECO Westinghouse

ISSUED	PERFORMANCE DATA	ENCLOSURE
8/28/2014	3-PHASE INDUCTION MOTOR	TEFC
TYPE		CATALOG#
AEHH8B		HB0024

NAMEPLATE INFORMATION

OUTPUT HP	OUTPUT KW	POLE	FRAME SIZE	VOLTAGE	HZ	RATED AMBIENT	INS. CLASS	NEMA DESIGN	TIME RATING	SERVICE FACTOR
2	1.5	4	145T	460	60	50°C	F	B	CONT.	1.15

VARIABLE FREQUENCY DRIVE SERVICE

VARIABLE TORQUE			
HZ	HP	RPM	TORQUE (lb-ft)
3~60	0.0003~2	90~1800	0.0175~6.035

OHMS/PHASE EQUIVALENT WYE CIRCUIT (AT RATED OPERATING TEMPERATURE 25°C)				
R1	R2	X1	X2	X_m
3.9555	4.3639	10.417	6.5877	170.99

CONSTANT TORQUE				CONSTANT HORSEPOWER			
HZ	HP	RPM	TORQUE (lb-ft)	HZ	HP	RPM	TORQUE (lb-ft)
6~60	.2~2	180~1800	6.035	60~120	2	1800~3600	6.035~3.0175

TYPICAL PERFORMANCE

FULL LOAD RPM	EFFICIENCY FULL LOAD MIN.%	EFFICIENCY FULL LOAD NOM.%	EFFICIENCY 3/4 LOAD %	EFFICIENCY 1/2 LOAD %	POWER FACTOR FULL LOAD %	POWER FACTOR 3/4 LOAD %	POWER FACTOR 1/2 LOAD %	SOUND PRESSURE LEVEL @ 3 FT Db(A)
1740	84	86.5	84	84	78	70	57	51

CURRENTS NO LOAD AT 460 VOLT	CURRENTS FULL LOAD AT 460 VOLT	CURRENTS LOCKED ROTOR AT 460 VOLT	NEMA KVA CODE LETTER	SAFE STALL TIME IN SECONDS COLD	SAFE STALL TIME IN SECONDS HOT
1.46	2.78	25	L	43	30

TORQUE FULL LOAD (lb-ft)	TORQUE LOCKED ROTOR %FLT	TORQUE PULL UP %FLT	TORQUE BREAK DOWN %FLT	INERTIA ROTOR WR^2 ($lb\text{-}ft^2$)	INERTIA NEMA LOAD WK^2 ($lb\text{-}ft^2$)	INERTIA MAX ALLOWABLE WK^2 ($lb\text{-}ft^2$)	ACCEL TIME (DOL) NEMA LOAD WK^2 Sec	ACCEL TIME (DOL) MAX ALLOWABLE WK^2 Sec	ALLOWABLE STARTS PER HOUR COLD	ALLOWABLE STARTS PER HOUR HOT
6.04	270	220	330	0.108	11	51	3.83	17.61	2	1

APPROVED:	M. PRATER	DRAWING NO.	31057HB0024	REVISION:	1

Downloaded from Dealers Industrial Equipment -- Visit https://DealersElectric.com or call (908) 688-1966 for all of your Teco needs