TECO Westinghouse

ISSUED	PERFORMANCE DATA	ENCLOSURE
May 3, 2011	3-PHASE INDUCTION MOTOR	TEFC
TYPE: AEHH8PCF		CATALOG#: NP0306C

NAMEPLATE INFORMATION

OUTPUT HP	OUTPUT KW	POLE	FRAME SIZE	VOLTAGE	HZ	RATED AMBIENT	INS. CLASS	NEMA DESIGN	TIME RATING	SERVICE FACTOR
30	22.4	6	326TC	190/380	50	40°C	F	B	CONT.	1.0

TYPICAL PERFORMANCE

FULL LOAD RPM	EFFICIENCY FULL LOAD MIN. %	EFFICIENCY FULL LOAD NOM. %	EFFICIENCY 3/4 LOAD %	EFFICIENCY 1/2 LOAD %	POWER FACTOR F. L. %	POWER FACTOR 3/4 LOAD %	POWER FACTOR 1/2 LOAD %	MAXIMUM POWER FACTOR CORRECTION
965	88.5	90.2	92.4	93	84.5	83.5	79	9.00 KVAR

CURRENTS NO LOAD AT 190 VOLT	NO LOAD	NO LOAD AT 380 VOLT	FULL LOAD AT 190 VOLT	FULL LOAD	FULL LOAD AT 380 VOLT	LOCKED ROTOR AT 190 VOLT	LOCKED ROTOR	LOCKED ROTOR AT 380 VOLT	NEMA KVA CODE LETTER
22.60		11.30	89.20		44.60	578.00		289.00	H

TORQUE FULL LOAD lb-ft	TORQUE LOCKED ROTOR %FLT	TORQUE PULL UP %FLT	TORQUE BREAK DOWN %FLT	INERTIA ROTOR WR^2 lb-ft^2	INERTIA NEMA LOAD WK^2 lb-ft^2	INERTIA MAX ALLOWABLE WK^2 lb-ft^2	ACCEL TIME NEMA LOAD WK^2 Sec	ACCEL TIME MAX ALLOWABLE WK^2 Sec
163.2	160	145	205	12.372	596.147	975.7142857	6.77	11.00

SAFE STALL TIME IN SECONDS COLD	SAFE STALL TIME IN SECONDS HOT	ALLOWABLE STARTS PER HOUR COLD	ALLOWABLE STARTS PER HOUR HOT	SOUND PRESSURE LEVEL @ 3 FT dB(A)
17	12	2	1	72

APPROVED:	M. PRATER	DRAWING NO.	31057NP0306C-50	REVISION 0

Downloaded from Dealers Industrial Equipment -- Visit https://DealersElectric.com or call (908) 688-1966 for all of your Teco needs!