

# TECO Westinghouse

ISSUED <p style="text-align: center; color: red;"><b>April 4, 2013</b></p>	<p style="color: red; font-size: 1.2em;"><b>PERFORMANCE DATA</b></p> <p style="font-size: 1.2em;"><b>3-PHASE INDUCTION MOTOR</b></p>	ENCLOSURE <p style="text-align: center; color: red;"><b>TEFC</b></p> CATALOG# <p style="text-align: center; color: red;"><b>WPV0024C</b></p>
TYPE <p style="text-align: center; color: red;"><b>AEGPVM</b></p>		

### NAMEPLATE INFORMATION

OUTPUT		POLE	FRAME SIZE	VOLTAGE	HZ	RATED AMBIENT	INS. CLASS	NEMA DESIGN	TIME RATING	SERVICE FACTOR
HP	KW									
<b>2.0</b>	<b>1.49</b>	<b>4</b>	<b>145TC</b>	<b>230/460</b>	<b>60</b>	<b>40°C</b>	<b>F</b>	<b>B</b>	<b>CONT.</b>	<b>1.15</b>

### TYPICAL PERFORMANCE

FULL LOAD RPM	EFFICIENCY				POWER FACTOR			MAXIMUM POWER FACTOR CORRECTION
	FULL LOAD		3/4 LOAD %	1/2 LOAD %	F. L. %	3/4 LOAD %	1/2 LOAD %	
	MIN. %	NOM. %						
<b>1760</b>	<b>86.5</b>	<b>84</b>	<b>86</b>	<b>84</b>	<b>75</b>	<b>65</b>	<b>50</b>	<b>1 KVAR</b>

### CURRENTS

NO LOAD			FULL LOAD			LOCKED ROTOR			NEMA KVA CODE LETTER
AT	AT	AT	AT	AT	AT	AT	AT	AT	
208 VOLT	230 VOLT	460 VOLT	208 VOLT	230 VOLT	460 VOLT	208 VOLT	230 VOLT	460 VOLT	
<b>3.87</b>	<b>3.50</b>	<b>1.75</b>	<b>6.20</b>	<b>6.00</b>	<b>3.00</b>	<b>55.29</b>	<b>50.00</b>	<b>25.00</b>	<b>L</b>

### TORQUE

### INERTIA

### ACCEL TIME

FULL LOAD lb-ft	LOCKED ROTOR %FLT	PULL UP %FLT	BREAK DOWN %FLT	ROTOR WR <sup>2</sup> lb-ft <sup>2</sup>	NEMA LOAD WK <sup>2</sup> lb-ft <sup>2</sup>	MAX ALLOWABLE WK <sup>2</sup> lb-ft <sup>2</sup>	NEMA LOAD WK <sup>2</sup> Sec	MAX ALLOWABLE WK <sup>2</sup> Sec

SAFE STALL TIME IN SECONDS		ALLOWABLE STARTS PER HOUR		SOUND PRESSURE LEVEL @ 3 FT dB(A)
COLD	HOT	COLD	HOT	
<b>12</b>	<b>10</b>	<b>2</b>	<b>1</b>	

APPROVED:	M. PRATER	DRAWING NO.	31057WPV0024C	REVISION	0
-----------	-----------	-------------	---------------	----------	---