

TECO Westinghouse

ISSUED <b style="color: red;">September 15, 2006	<b style="color: red; font-size: 1.2em;">PERFORMANCE DATA 3-PHASE INDUCTION MOTOR	ENCLOSURE <b style="color: red;">TEFC
TYPE <b style="color: red;">AEUHXF		CATALOG# <b style="color: red;">XV0306C-50

NAMEPLATE INFORMATION

OUTPUT		POLE	FRAME SIZE	VOLTAGE	HZ	RATED AMBIENT	INS. CLASS	NEMA DESIGN	TIME RATING	SERVICE FACTOR
HP	KW									
30	22.38	6	326TC	190/380	50	40°C	F	B	CONT.	1.00

TYPICAL PERFORMANCE

FULL LOAD RPM	EFFICIENCY				POWER FACTOR		
	FULL LOAD		3/4 LOAD	1/2 LOAD	F. L.	3/4 LOAD	1/2 LOAD
	MIN. %	NOM. %	%	%	%	%	%
965	88.5	90.2	92	93	84	83	79

CURRENTS

NO LOAD		FULL LOAD		LOCKED ROTOR		NEMA KVA CODE LETTER
AT 190 VOLTS	AT 380 VOLTS	AT 190 VOLTS	AT 380 VOLTS	AT 190 VOLTS	AT 380 VOLTS	
24.00	12.00	89.76	44.88	578.00	289.00	

TORQUE

INERTIA

ACCEL TIME

FULL LOAD lb-ft	LOCKED ROTOR %FLT	PULL UP %FLT	BREAK DOWN %FLT	ROTOR WR ² lb-ft ²	NEMA LOAD WK ² lb-ft ²	MAX ALLOWABLE WK ² lb-ft ²	NEMA LOAD WK ² Sec	MAX ALLOWABLE WK ² Sec
163.23	160	140	185	12.372	596.15	957.17	7.19	11.45

SAFE STALL TIME IN SECONDS

ALLOWABLE STARTS PER HOUR

SOUND PRESSURE LEVEL @ 3 FT dB(A)

COLD	HOT	COLD	HOT
30	15	2	1

APPROVED:	<b style="color: red;">M. PRATER	DRAWING NO.	<b style="color: red;">31057XV0306C-50	REVISION	<b style="color: red; font-size: 1.2em;">0
-----------	--------------------------------------	-------------	--	----------	--