



NOTE: -  
 TERMINAL BOX CAN BE TOP OR RIGHT  
 HAND SIDE MOUNTED BY REFITTING FEET  
 90° IN APPROPRIATE DIRECTION.  
 CABLE ENTRY CAN BE SUPPLIED IN  
 ANY ONE OF FOUR POSITIONS AT  
 90° INTERVALS.

CUSTOMER		
ORDER No.		
SERIAL No.		
FRAME SIZE		
HP	RPM.	
Hz	PHASE 3	
VOLTS	POLES	
BRGS.	DE.	NDE.
MOTOR NETT. WT.	Kg.	
INSULATION CLASS		
TEMPERATURE RISE °C		
DESIGN AMBIENT TEMPERATURE °C		
HEATER WATTS & VOLTS		
WATTS,		VOLTS

REMARKS

**BROOK CROMPTON**  
 PRELIMINARY

Large Industrial Motors  
 Guiseley, LEEDS LS20 9NZ

ALL DIMENSIONS IN INCHES



THIRD ANGLE  
 PROJECTION

**BROOK CROMPTON**

Large Industrial Motors  
 GUISELEY, LEEDS, LS20 9NZ.

NOTE 1  
 \* ENDPLAY WILL BE PROVIDED FOR ENDRUSTR  
 PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR  
 INTENTION TO USE RIGID COUPLINGS AND DRIVEN  
 MACHINES WITHOUT ENDPLAY.

OUTLINE DIMENSIONS OF STANDARD FOOT MOUNTED INCH A. C. MOTOR  
 TO NEMA STD. MG1. TOTALLY ENCLOSED FAN COOLED.  
 FITTED WITH SIDE MOUNTED TERMINAL BOX  
 FRAME SIZE :- W-DF405TS-N (2 POLE)

SCALE	1:8	DATE
DRAWN	B. J. T.	23.2.94
CHECKED	B. J. T.	23.2.94
APPROVED	I. J. W.	23.2.94

DRG. No.	M9549	
REVISION:		DATE