

NOTE: -
 TERMINAL BOX CAN BE TOP OR RIGHT
 HAND SIDE MOUNTED BY REFITTING FEET
 90° IN APPROPRIATE DIRECTION.
 CABLE ENTRY CAN BE SUPPLIED IN
 ANY ONE OF FOUR POSITIONS AT
 90° INTERVALS.

NOTE !
 2.5 ENDPLAY WILL BE PROVIDED FOR ENDTHRUST
 PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR
 INTENTION TO USE RIGID COUPLINGS AND DRIVEN
 MACHINES WITHOUT ENDPLAY.


OUTLINE DIMENSIONS OF STANDARD FOOT MOUNTED INCH A. C. MOTOR
 TO NEMA STD. MG1. TOTALLY ENCLOSED FAN COOLED.
 FITTED WITH SIDE MOUNTED TERMINAL BOX
 FRAME SIZE: W-DF445TS-E (4 POLE UP.)

SCALE	1:8	DATE
DRAWN	M.E	5.7.00
CHECKED	J.M.L	5.7.00
APPROVED	J.M.L	5.7.00

CUSTOMER		
ORDER No.		
SERIAL No.		
FRAME SIZE		
kw	RPM.	
Hz	PHASE 3	
VOLTS	POLES	
BRGS.	DE.	NDE.
MOTOR NETT. WT.	Kg.	
INSULATION CLASS		
TEMPERATURE RISE	°C	
DESIGN AMBIENT TEMPERATURE	°C	
HEATER WATTS & VOLTS	WATTS,	VOLTS

REMARKS

ALL DIMENSIONS IN MILLIMETRES



FIRST ANGLE
 PROJECTION

DRG. No.	M22082
REVISION:	DATE