



NOTE: -  
 TERMINAL BOX CAN BE TOP OR RIGHT  
 HAND SIDE MOUNTED BY REFITTING FEET  
 90° IN APPROPRIATE DIRECTION.  
 CABLE ENTRY CAN BE SUPPLIED IN  
 ANY ONE OF FOUR POSITIONS AT  
 90° INTERVALS.

CUSTOMER		
ORDER No.		
SERIAL No.		
FRAME SIZE		
HP	RPM.	
Hz	PHASE 3	
VOLTS	POLES	
BRGS.	DE.	NDE.
MOTOR NETT. WT.	Kg.	
INSULATION CLASS		
TEMPERATURE RISE °C		
DESIGN AMBIENT TEMPERATURE °C		
HEATER WATTS & VOLTS		
WATTS, VOLTS		

REMARKS

ALL DIMENSIONS IN INCHES



THIRD ANGLE  
 PROJECTION

NOTE !  
 \* ENDPLAY WILL BE PROVIDED FOR ENDTHRUST  
 PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR  
 INTENTION TO USE RIGID COUPLINGS AND DRIVEN  
 MACHINES WITHOUT ENDTPLAY.

OUTLINE DIMENSIONS OF STANDARD FOOT/D FLANGE MOUNTED INCH A. C. MOTOR  
 TO NEMA STD. MG1. TOTALLY ENCLOSED FAN COOLED.  
 FITTED WITH SIDE MOUNTED TERMINAL BOX  
 FRAME SIZE :- W-DF445TS-N (4 POLE UP)

SCALE	1:8	DATE
DRAWN	BTT/mons	9.2.94
CHECKED	B. J. T.	9.2.94
APPROVED	I. J. W.	9.2.94

DRG. No.	M9523	
REVISION:		DATE