



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET

Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase : IEC Tru-Metric - TEFC (IP55) - Aluminum Frame

Frame : 80
 Output : 0.25 HP
 Frequency : 60 Hz
 Poles : 8
 Full load speed : 860 rpm
 Slip : 4.44 %
 Voltage : 460 V
 Rated current : 0.799 A
 Locked rotor current : 2.64 A
 Locked rotor current (I_L/I_n) : 3.3
 No-load current : 0.810 A
 Full load torque : 1.51 lb.ft
 Locked rotor torque : 200 %
 Breakdown torque : 240 %
 Design : ---
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 8 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 25 lb
 Moment of inertia : 0.05743 sq.ft.lb
 Noise level : 46 dB(A)

	D.E.	N.D.E.
Bearings	6204 ZZ	6203 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.56	50.5
75%	0.48	43.3
50%	0.40	34.6

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #.1809EP3WAL80

Performed by

Checked