



# Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Three Phase: W01 (Rolled Steel) - ODP - Standard Efficiency

Frame : 56  
 Output : 0.25 HP  
 Frequency : 60 Hz  
 Poles : 6  
 Full load speed : 1160 rpm  
 Slip : 3.33 %  
 Voltage : 208-230/460 V  
 Rated current : 1.32-1.20/0.598 A  
 Locked rotor current : 5.38/2.69 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 4.5  
 No-load current : 1.08/0.538 A  
 Full load torque : 1.12 lb.ft  
 Locked rotor torque : 210 %  
 Breakdown torque : 300 %  
 Design : A  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 37 s (hot)  
 Service factor : 1.35  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : ODP  
 Approximate weight : 17 lb  
 Moment of inertia : 0.06217 sq.ft.lb  
 Noise level : 50 dB(A)

	D.E.	N.D.E.
Bearings	6203 ZZ	6202 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.59	64.0
75%	0.51	60.0
50%	0.41	52.5

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #.2512OS3E56-S

Performed by

Checked