



# Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
Product line : Three-Phase : NEMA 56 Frames - ODP

Frame : A56  
Output : 0.25 HP  
Frequency : 60 Hz  
Poles : 6  
Full load speed : 1150 rpm  
Slip : 4.17 %  
Voltage : 208-230/460 V  
Rated current : 1.33-1.50/0.750 A  
Locked rotor current : 5.70/2.85 A  
Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 3.8  
No-load current : 1.40/0.700 A  
Full load torque : 1.13 lb.ft  
Locked rotor torque : 280 %  
Breakdown torque : 310 %  
Design : A  
Insulation class : B  
Temperature rise : 80 K  
Locked rotor time : 15 s (hot)  
Service factor : 1.35 (1.00 at 208V)  
Duty cycle : S1  
Ambient temperature : -20°C - +40°C  
Altitude : 1000 m  
Degree of Protection : IP21  
Approximate weight : 18 lb  
Moment of inertia : 0.04556 sq.ft.lb  
Noise level : ---

	D.E.	N.D.E.
Bearings	6204 ZZ	6203 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.59	55.0
75%	0.52	50.0
50%	0.43	40.0

Notes:  
Downloaded from <http://dealerselectric.com>  
Generated for Model #.2512OS3EA56C

Performed by

Checked