



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : Three-Phase : NEMA 56 Frames - ODP

Frame : A56
Output : 0.25 HP
Frequency : 60 Hz
Poles : 4
Full load speed : 1750 rpm
Slip : 2.78 %
Voltage : 208-230/460 V
Rated current : 1.20-1.21/0.607 A
Locked rotor current : 6.68/3.34 A
Locked rotor current (I_L/I_n) : 5.5
No-load current : 1.20/0.600 A
Full load torque : 0.740 lb.ft
Locked rotor torque : 290 %
Breakdown torque : 380 %
Design : A
Insulation class : B
Temperature rise : 80 K
Locked rotor time : 15 s (hot)
Service factor : 1.35 (1.00 at 208V)
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP21
Approximate weight : 21 lb
Moment of inertia : 0.03868 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.
Bearings	6204 ZZ	6203 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.60	62.0
75%	0.52	57.5
50%	0.44	50.5

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #.2518OS3EA56

Performed by

Checked