



# Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

## DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Single-Phase : NEMA 48 & 56 ODP - Start Capacitor

Frame : B48  
 Output : 0.25 HP  
 Frequency : 60 Hz  
 Poles : 2  
 Full load speed : 3440 rpm  
 Slip : 4.44 %  
 Voltage : 115/208-230 V  
 Rated current : 4.30/2.10-2.15 A  
 Locked rotor current : 21.9/11.0 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 5.1  
 No-load current : 3.10/1.55 A  
 Full load torque : 0.377 lb.ft  
 Locked rotor torque : 350 %  
 Breakdown torque : 280 %  
 Design : ---  
 Insulation class : B  
 Temperature rise : 80 K  
 Locked rotor time : 6 s (hot)  
 Service factor : 1.35 (1.00 at 208V)  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : IP21  
 Approximate weight : 18 lb  
 Moment of inertia : 0.01495 sq.ft.lb  
 Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6203 ZZ	6202 ZZ	100%	0.68	54.7
Regreasing interval	---	---	75%	0.64	50.5
Grease amount	---	---	50%	0.56	42.0

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #.2536OS1BB48

Performed by

Checked