



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three Phase: W01 (Rolled Steel) - ODP - Standard Efficiency

Frame : 56
 Output : 0.25 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3520 rpm
 Slip : 2.22 %
 Voltage : 208-230/460 V
 Rated current : 1.08-0.980/0.490 A
 Locked rotor current : 6.86/3.43 A
 Locked rotor current (I_L/I_n) : 7.0
 No-load current : 0.660/0.330 A
 Full load torque : 0.368 lb.ft
 Locked rotor torque : 280 %
 Breakdown torque : 360 %
 Design : A
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 48 s (hot)
 Service factor : 1.35
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : ODP
 Approximate weight : 16 lb
 Moment of inertia : 0.03892 sq.ft.lb
 Noise level : 62 dB(A)

	D.E.	N.D.E.
Bearings	6203 ZZ	6202 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.72	64.0
75%	0.64	62.0
50%	0.53	52.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #.2536OS3E56-S

Performed by

Checked