



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Single-Phase : NEMA 48 & 56 ODP - Start Capacitor

Frame : C48
 Output : 0.33 HP
 Frequency : 60 Hz
 Poles : 4
 Full load speed : 1740 rpm
 Slip : 3.33 %
 Voltage : 115/208-230 V
 Rated current : 6.21/3.11 A
 Locked rotor current : 29.8/14.9 A
 Locked rotor current (I_L/I_n) : 4.8
 No-load current : 5.06/2.53 A
 Full load torque : 0.983 lb.ft
 Locked rotor torque : 320 %
 Breakdown torque : 270 %
 Design : ---
 Insulation class : B
 Temperature rise : 80 K
 Locked rotor time : 6 s (hot)
 Service factor : 1.35 (1.00 at 208V)
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP21
 Approximate weight : 21 lb
 Moment of inertia : 0.04010 sq.ft.lb
 Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6203 ZZ	6202 ZZ	100%	0.58	58.6
Regreasing interval	---	---	75%	0.51	55.0
Grease amount	---	---	50%	0.42	47.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #.3318OS1BC48

Performed by

Checked