



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Single-phase induction motor - Squirrel cage rotor

Customer :
Product line : Single-Phase : NEMA 48 & 56 ODP - Start Capacitor

Frame : C48
Output : 0.33 HP
Frequency : 60 Hz
Poles : 4
Full load speed : 1740 rpm
Slip : 3.33 %
Voltage : 115/208-230 V
Rated current : 6.21/3.11 A
Locked rotor current : 29.8/14.9 A
Locked rotor current (I_L/I_n) : 4.8
No-load current : 5.06/2.53 A
Full load torque : 0.983 lb.ft
Locked rotor torque : 320 %
Breakdown torque : 270 %
Design : ---
Insulation class : B
Temperature rise : 80 K
Locked rotor time : 6 s (hot)
Service factor : 1.35 (1.00 at 208V)
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP21
Approximate weight : 21 lb
Moment of inertia : 0.04010 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.
Bearings	6203 ZZ	6202 ZZ
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.58	58.6
75%	0.51	55.0
50%	0.42	47.0

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #.3318OS1BC48C

Performed by

Checked