



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET

Single-phase induction motor - Squirrel cage rotor

Customer :
Product line : Single-Phase : NEMA 48 & 56 ODP - Start Capacitor

Frame : C56
Output : 0.33 HP
Frequency : 60 Hz
Poles : 4
Full load speed : 1745 rpm
Slip : 3.06 %
Voltage : 115/208-230 V
Rated current : 6.60/3.10-3.30 A
Locked rotor current : 34.3/17.2 A
Locked rotor current (I_L/I_n) : 5.2
No-load current : 5.60/2.80 A
Full load torque : 0.980 lb.ft
Locked rotor torque : 350 %
Breakdown torque : 280 %
Design : ---
Insulation class : B
Temperature rise : 80 K
Locked rotor time : 6 s (hot)
Service factor : 1.35 (1.00 at 208V)
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP21
Approximate weight : 22 lb
Moment of inertia : 0.04010 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6203 ZZ	6202 ZZ	100%	0.55	58.2
Regreasing interval	---	---	75%	0.47	53.5
Grease amount	---	---	50%	0.39	45.5

Notes:

Downloaded from <http://dealerselectric.com>
Generated for Model #.3318OS1BC56CFL

Performed by

Checked