



Dealers Industrial Equipment

No.:

Date: 12-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : Three-Phase : NEMA 56 Frames - ODP

Frame : A56
Output : 0.33 HP
Frequency : 60 Hz
Poles : 4
Full load speed : 1740 rpm
Slip : 3.33 %
Voltage : 208-230/460 V
Rated current : 1.30-1.42/0.711 A
Locked rotor current : 8.11/4.05 A
Locked rotor current (I_L/I_n) : 5.7
No-load current : 1.20/0.600 A
Full load torque : 0.983 lb.ft
Locked rotor torque : 230 %
Breakdown torque : 290 %
Design : A
Insulation class : B
Temperature rise : 80 K
Locked rotor time : 15 s (hot)
Service factor : 1.35 (1.00 at 208V)
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP21
Approximate weight : 22 lb
Moment of inertia : 0.03868 sq.ft.lb
Noise level : ---

| | D.E. | N.D.E. |
|---------------------|---------|---------|
| Bearings | 6204 ZZ | 6203 ZZ |
| Regreasing interval | --- | --- |
| Grease amount | --- | --- |

| Load | Power factor | Efficiency (%) |
|------|--------------|----------------|
| 100% | 0.69 | 64.0 |
| 75% | 0.57 | 62.0 |
| 50% | 0.47 | 52.5 |

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #.3318OS3EA56CFL

Performed by

Checked